
LED T8-RetroFit
RL-T8 58 S 27W/840/G13

Radium

Product Datasheet Date: 10.11.2026





A+	C	3400	4000K	50 000h

General Data

Artikel Nr.	42918016
Bestellzeichen	RL-T8 58 S 27W/840/G13
EAN-Faltschachtel	4008597180163
Versandeinheit in Stk.	25
EAN Umkarton (Versandeinheit)	4008597480164
Brutto-Gewicht Versandeinheit in kg	10.316
Länge Versandeinheit in m	1.64
Breite Versandeinheit in m	0.17
Höhe Versandeinheit in m	0.18
Product weight	285 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	27.0 W
Power factor	> 0,9
Power factor	0.7
Nominal voltage	220-240 V
Voltage type	AC

LED T8-RetroFit
RL-T8 58 S 27W/840/G13

Radium

Electric Parameters

max. no. of lamps at 10A-B10 automatic fuse	56
max. no. of lamps at 16A-B16 automatic fuse	90
dimmable	Nein

Light Application Parameters

Rated lamp luminous flux	3400 lm
Luminous flux in 90°-sector	3400 lm
Beam angle	150 °
Efficacy / Luminous efficiency	125.93 lm/W
Color temperature	4000 K
Color rendering index	> 80
Color Stability	≤ 6 sdcm

Service Life

Average life	50000 h
Mean service life	50000 h
No. switching cycles	200000

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	C
Energylabel (E -> A++)	A+
Diameter	28 mm
Tube diameter	26 mm
Length	1500 mm
Length	1500 mm
Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, double-ended
Base	G13
Material	Glass
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any

LED T8-RetroFit
RL-T8 58 S 27W/840/G13

Radium

Notes on Operation

Mode of operation	CCG, 230V
Ambient temperatures	-20 ... +45°C
With movement sensor	Nein

Information especially for EPREL


Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Displacement factor EPREL	0,7
Life factor EPREL	0.9
Lumen maintenance EPREL	0.96
Flicker	1.0
Stroboscopic effect	0.4

Notes

T8 tubular LED lamp for exchange with fluorescent lamps, neutral white light, plastic body, non-dim, base G13. Please, note installation instructions!


Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


Sockelübersicht



G13
IEC/EN 60061-1
sheet 7004-51-8

Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.





LED T8-RetroFit
RL-T8 58 S 27W/840/G13

LED retrofit tube lamps for fluorescent lamps 4000K daylight(D 65)

Besonderheiten



Allgemeine Hinweise
Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.