
LED Essence Tube
RL-T8 18 9W/840/G13

Radium

Product Datasheet Date: 10.11.2026





A+	G	750	4000K	30 000h

General Data

Artikel Nr.	43018488
Bestellzeichen	RL-T8 18 840 EM
EAN-Faltschachtel	4008597184888
Versandeinheit in Stk.	25
EAN Umkarton (Versandeinheit)	4008597484889
Brutto-Gewicht Versandeinheit in kg	4.193
Länge Versandeinheit in m	0.74
Breite Versandeinheit in m	0.21
Höhe Versandeinheit in m	0.22
Product weight	120 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	9.0 W
Weighted energy consumption in 1000 hours	9 kWh
Lamp power	9.0-9.0 W
Power factor	> 0,9
Power factor	0.9

LED Essence Tube
RL-T8 18 9W/840/G13

Radium

Electric Parameters

Nominal voltage	220-240 V
Voltage type	AC
Nominal current	43-43 mA
Nominal current (mA)	43 mA
dimmable	Nein

Light Application Parameters

Rated lamp luminous flux	750 lm
Beam angle	190 °
Efficacy / Luminous efficiency	83.33 lm/W
Total mains efficacy	83.33 lm/W
Light colour	white
Color temperature	4000 K
Color rendering index	≥ 80
Color Stability	≤ 6 sdcm

Service Life

Average life	30000 h
Mean service life	30000 h
Min. number of switching cycles	200000

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	A+
Diameter	28 mm
Tube diameter	26 mm
Length	602 mm
Length	590 mm
Burning position	any
Mercury content	0.0 mg
Shatterproof	Nein
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, double-ended
Base	G13
Material	Glass

LED Essence Tube
RL-T8 18 9W/840/G13

Radium

Specification

Colour	White
Housing colour	White

Notes on Operation

IP Class (Room/Ceiling)	IP20
Burning position	any
Mode of operation	CCG, 230V
Range of storage temperature	-20…+80 °C
Ambient temperatures	-20 ... +45°C
With movement sensor	Nein

Information especially for EPREL


Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Displacement factor EPREL	0,7
Life factor EPREL	0.9
Lumen maintenance EPREL	0.96
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	917294

Notes

T8 tubular LED lamp for exchange with fluorescent lamps, neutral white light, plastic body, non-dim, base G13. Please, note installation instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht




G13
IEC/EN 60061-1
sheet 7004-51-8


Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

LED Essence Tube
RL-T8 18 9W/840/G13

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit tube lamps for fluorescent lamps 4000K



daylight(D 65)

Besonderheiten



Allgemeine Hinweise
Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.