
Aluminium F-profile for 2 LED stripes

Track PRO-F 46/25/T22I



Product Datasheet Date: 05.11.2025





General Data

Artikel Nr.	TRPA1849
Bestellzeichen	PROFILE M WING 46/25/B5C5 P 3M
EAN-Faltschachtel	4052899448773
Versandeinheit in Stk.	4
EAN Umkarton (Versandeinheit)	4052899448780
Brutto-Gewicht Versandeinheit in kg	5.116
Länge Versandeinheit in m	3.02
Breite Versandeinheit in m	0.15
Höhe Versandeinheit in m	0.15
Product weight	929 g
Produktstatus	Aktiv

Specification

Length max. 3000 mm Length 3 m Height 25 mm Width 46 mm Built-in width 26.5 mm Internal width 24 mm Material Aluminium no. of LED stripes in profile 2	Type of accessory/spare part	Profile
Height 25 mm Width 46 mm Built-in width 26.5 mm Internal width 24 mm Material Aluminium no. of LED stripes in profile 2	Length max.	3000 mm
Width46 mmBuilt-in width26.5 mmInternal width24 mmMaterialAluminiumno. of LED stripes in profile2	Length	3 m
Built-in width26.5 mmInternal width24 mmMaterialAluminiumno. of LED stripes in profile2	Height	25 mm
Internal width 24 mm Material Aluminium no. of LED stripes in profile 2	Width	46 mm
Material Aluminium no. of LED stripes in profile 2	Built-in width	26.5 mm
no. of LED stripes in profile 2	Internal width	24 mm
	Material	Aluminium
	no. of LED stripes in profile	2
Product shape F	Product shape	F

Aluminium F-profile for 2 LED stripes

Track PRO-F 46/25/T22I



Notes on Operation

Fitting Endcap	ZTPA2616, ZTPA2619, ZTPA4962
Fitting Cover	ZTPA1852
Fitting mounting clips or suspension	ZTPA1856

Notes

For cooling and protection of LED strips, width for 2 LED strips, suitable for various types of mounting (clips, springs, etc.), length adjustable.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.