

LED linear lamp, opal

RL-RAL2 120 DIM 15W/230/827/O/S14S

Radium

Product Datasheet Date: 10.11.2026





W	lm		h	
15	1000	2700K	20 000h	Dimmbar

General Data

Artikel Nr.	42614817
Bestellzeichen	RL-RAL2 120 DIM 827/O
EAN-Faltschachtel	4008597148170
Versandeinheit in Stk.	5
EAN Umkarton (Versandeinheit)	4008597448171
Brutto-Gewicht Versandeinheit in kg	1.995
Länge Versandeinheit in m	1.06
Breite Versandeinheit in m	0.278
Höhe Versandeinheit in m	0.087
Product weight	210 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	15.0 W
Nominal power	15.0 W
Weighted energy consumption in 1000 hours	15 kWh
Lamp power	15.0-15.0 W
Power factor	≥ 0.9

LED linear lamp, opal

RL-RAL2 120 DIM 15W/230/827/O/S14S

Radium

Electric Parameters

Power factor	0.9
Nominal voltage	220-240 V
Mains Voltage	220 - 240 V
Voltage type	AC
Nominal current	73-73 mA
Nominal current (mA)	73 mA
dimmable	Ja

Light Application Parameters

Rated lamp luminous flux	1000 lm
Luminous flux in 90°-sector	1000 lm
Beam angle	200 °
Efficacy / Luminous efficiency	66,67 lm/W
Total mains efficacy	66.67 lm/W
Light colour	warm white
Color temperature	2700 K
Colour rendering index CRI	80-89
Color Stability	≤ 6 sdcm

Service Life

Average life	20000 h
Mean service life	25000 h
Min. number of switching cycles	100000

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Diameter	29 mm
Length	1000 mm
Length	1000 mm
Burning position	any
Mercury content	0.0 mg
Lamp shape	Linear
Base	S14s
Material	Glass
Colour	White
Housing colour	White

LED linear lamp, opal
RL-RAL2 120 DIM 15W/230/827/O/S14S

Radium

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Ambient temperatures	-20…+40 °C
With movement sensor	Nein

Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Directional or non-directional light	NDLS
Type of color temperature	SINGLE_VALUE
Life factor EPREL	0.9
Lumen maintenance EPREL	0.93

Notes

RaLEDina, LED lamp for exchange with linear incandescent lamps, coated glass bulb, dimmable, base S14s. LED light does not contain UV or IR radiation.


Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht




S14s
IEC/EN 60061-1
sheet 7004-112-1

Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



RaLEDina: LED retrofit for Linear incandescent lamp 2700K




daylight(D 65)

Besonderheiten

LED linear lamp, opal

RL-RAL2 120 DIM 15W/230/827/O/S14S











Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.