
LED Essence PIN
RL-PIN28 827/C/GY6.35

Radium

Product Datasheet Date: 10.11.2026





A++	E	2,4	300	2700K	15 000h	4 YEARS GUARANTEE

General Data

Artikel Nr.	43618552
Bestellzeichen	RL-PIN28 827/C/GY6.35
EAN-Faltschachtel	4008597185526
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4008597485527
Brutto-Gewicht Versandeinheit in kg	0.201
Länge Versandeinheit in m	1.49
Breite Versandeinheit in m	1.21
Höhe Versandeinheit in m	0.73
Product weight	6 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	2.4 W
Nominal power	2.4 W
Weighted energy consumption in 1000 hours	3 kWh
Lamp power	2.4-2.4 W
Power factor	0.50

LED Essence PIN
RL-PIN28 827/C/GY6.35

Radium

Electric Parameters

Power factor	0,5
Nominal voltage	11.5-12 V
Voltage type	AC
Nominal current	300-300 mA
Nominal current (mA)	300 mA
max. no. of lamps at 10A-B10 automatic fuse	23
max. no. of lamps at 16A-B16 automatic fuse	37
dimmable	Nein

Light Application Parameters

Luminous flux	300 lm
Rated lamp luminous flux	300 lm
Luminous flux in 90°-sector	300 lm lm
Luminous flux in 120°-sector	300 lm lm
Beam angle	300 °
Efficacy / Luminous efficiency	125 lm/W
Total mains efficacy	125 lm/W
Light colour	warmwhite
Color temperature	2700 K
Colour rendering index CRI	80-89
Color rendering index nominal	80-89

Service Life

Average life	15000 h
Mean service life	15000 h
No. switching cycles	[100000]
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	4 years

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	E
Energylabel (E -> A++)	A++
Diameter	13 mm
Length max.	57 mm mm

LED Essence PIN
RL-PIN28 827/C/GY6.35

Radium

Specification

Length	57 mm
Burning position	any
Mercury content	0.0 mg
Lamp shape	Capsule
Base	GY6.35
Colour	White
Housing colour	Other

Notes on Operation

IP Class (Room/Ceiling)	IP20
Burning position	any
Mode of operation	LV transformer
Ambient temperatures	-20…+40 °C
With movement sensor	Nein

Information especially for EPREL


Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Color tunable light source	Nein
Life factor EPREL	0.9
Lumen maintenance EPREL	0.93
EPREL ID number	875497

Notes

LED PIN, LED lamp for exchange with pin-base halogen lamps, base GY6.35. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


Sockelübersicht




GY6.35
IEC/EN 60061-1
sheet 7004-59-6

Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not

need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED-Retrofit-Lamps 2700K



daylight(D 65)

Besonderheiten









Allgemeine Hinweise
For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.