



General Data

Artikel Nr.	OTDA2462
Bestellzeichen	DRIVER BT 4CH 80W/24V IP20 OSRAM
EAN-Faltschachtel	4062172046558
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4062172046565
Brutto-Gewicht Versandeinheit in kg	4.034
Product weight	191 g
Produktstatus	● PhaseOut

Electric Parameters

Rated value output power max.	80.0 W
min. output power	0.8 W
Output power	0-80.0 W
Power factor	0,98
Input voltage AC (range)	198-264 V
Output Voltage	24,2 V
Output voltage	24-24 V
Surge voltage resistance (L - N)	1 kV
Number of Channels	4
Supply frequency	50/60 Hz
max. no. of lamps at 10A-B10 automatic fuse	11
max. no. of lamps at 16A-B16 automatic fuse	17
dimnable	Ja

Electric Parameters

Dimming with push-button	Nein
Dimming interface	Bluetooth

Service Life

Service life	50000 h
Tc Temperature max.	65 °C

Specification

Mean efficiency	93 %
Length	346 mm
Height max.	22 mm
Width	32 mm
Material	Plastic
Model	Static

Notes on Operation

Degree of protection (IP)	IP20
Type of connection	screw clamp
Ambient temperatures	-20...+45 °C
Tc Temperature max.	65 °C

Notes

4 channel constant voltage supply 24V, dimmable via Bluetooth using the CASAMBI App, for indoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage. The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Besonderheiten



Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or

LED driver Bluetooth

DRIVER BT 4CH 80W/24V IP20 OSRAM

Radium

even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.