# **LED driver DALI**DRIVER DALI 4CH 210W/24V IP67 OSRAM



Product Datasheet Date: 05.11.2025



### **General Data**

Artikel Nr.	OTDA2461
Bestellzeichen	DRIVER DALI 4CH 210W/24V IP67 OSRAM
EAN-Faltschachtel	4062172032087
Versandeinheit in Stk.	6
EAN Umkarton (Versandeinheit)	4062172032094
Brutto-Gewicht Versandeinheit in kg	9.195
Product weight	1468 g
Produktstatus	Aktiv

### **Electric Parameters**

## **LED driver DALI**

## DRIVER DALI 4CH 210W/24V IP67 OSRAM



#### **Electric Parameters**

dimmable	Ja
Dimming with push-button	Nein
Dimming interface	DALI
DALI Device Type	DT6

#### **Service Life**

Service life	30000 h
Tc Temperature max.	85 °C

### **Specification**

Mean efficiency	93 %
Length	330 mm
Height max.	37 mm
Width	69 mm
Material	Aluminium
Model	Static

## **Notes on Operation**

Degree of protection (IP)	IP67
Type of connection	Cable
Ambient temperatures	-30+60 °C
Tc Temperature max.	85 °C

#### **Notes**

4 channel constant voltage supply 24V, dimmable via DALI interface, for outdoor applications

Please, refer to <a href="www.radium.de/recycling">www.radium.de/recycling</a> for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains

(frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Besonderheiten



#### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your

# **LED driver DALI**DRIVER DALI 4CH 210W/24V IP67 OSRAM



quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.