



## General Data

Artikel Nr.	OTDA1725
Bestellzeichen	DRIVER DALI TW 50W/24V IP20 OSRAM
EAN-Faltschachtel	4052899490772
Versandereinheit in Stk.	20
EAN Umkarton (Versandereinheit)	4052899490789
Brutto-Gewicht Versandereinheit in kg	3.998
Länge Versandereinheit in m	0.37
Breite Versandereinheit in m	0.17
Höhe Versandereinheit in m	0.12
Product weight	191 g
Produktstatus	<span style="color: red;">●</span> Inaktiv

## Electric Parameters

Rated value output power max.	50.0 W
min. output power	0.5 W
Output power	0-50.0 W
Power factor	0,98
Input voltage AC (range)	198-264 V
Output Voltage	24,2 V
Output voltage	24-24 V
Surge voltage resistance (L - N)	1 kV
Number of Channels	2
Supply frequency	0/50/60 Hz

# LED driver DALI

DRIVER DALI TW 50W/24V IP20 OSRAM

**Radium**

## Electric Parameters

max. no. of lamps at 10A-B10 automatic fuse	9
max. no. of lamps at 16A-B16 automatic fuse	15
dimmable	Ja
Dimming with push-button	Ja
Dimming interface	DALI
DALI Device Type	DT8

## Service Life

Service life	50000 h
Tc Temperature max.	70 °C

## Specification

Mean efficiency	92 %
Length	345 mm
Height max.	22 mm
Width	32 mm
Material	Plastic
Model	Static

## Notes on Operation

Degree of protection (IP)	IP20
Type of connection	screw clamp
Ambient temperatures	-20...+45 °C
Tc Temperature max.	70 °C

## Notes

Tunable White constant voltage supply 24V, dimmable via DALI interface (DT8), for indoor applications

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

## Besonderheiten



## Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case

## LED driver DALI

DRIVER DALI TW 50W/24V IP20 OSRAM

**Radium**

of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

**All technical data without guarantee.**