



General Data

Artikel Nr.	LMBA2700
Bestellzeichen	MOUNTING PACK BCU 150/TED
EAN-Faltschachtel	4003556008960
Versandereinheit in Stk.	100
EAN Umkarton (Versandereinheit)	4003556408968
Brutto-Gewicht Versandereinheit in kg	6
Länge Versandereinheit in m	0.34
Breite Versandereinheit in m	0.29
Höhe Versandereinheit in m	0.16
Product weight	44 g
Produktstatus	● Aktiv

Electric Parameters

Number of Channels	1
Mains frequency	50...60 Hz
Power controlled max.	150.0 W
max. load halogen lamps	150.0 W
Dimming interface	Bluetooth

Specification

Length	81 mm
Height max.	28.2 mm
Height	28.2 mm
Width	52 mm

Specification

Model	Electronic light controller
-------	-----------------------------

Notes on Operation

protection class (IP)	IP20
max. relative air humidity	80 %

Miscellaneous

Similar products	LMBA0027, LMZA2701, LMBA4953
------------------	------------------------------

Notes

Electronic mini trailing edge dimmer for 230V mains, in mounting case, implementation and operation via APP, also retrievable via switch.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Besonderheiten



Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.