

Product Datasheet Date: 05.11.2025

















A++

Ε

4000

4000K

50 000h

General Data

Artikel Nr.	43819349
Bestellzeichen	RL-HRL80 840/E27
EAN-Faltschachtel	4008597193491
Versandeinheit in Stk.	6
Brutto-Gewicht Versandeinheit in kg	3.335
Länge Versandeinheit in m	0.335
Breite Versandeinheit in m	0.23
Höhe Versandeinheit in m	0.22
Product weight	380 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	30.0 W
Nominal power	30.0 W
Weighted energy consumption in 1000 hours	30 kWh
Lamp power	30.0-30.0 W
Power factor	0.90
Nominal voltage	220-240 V

LED HPM-Retrofit

RL-HRL80 840/E27



Electric Parameters

Mains Voltage	220 - 240 V
Voltage type	AC
Nominal current	136-136 mA
Nominal current (mA)	136 mA
max. no. of lamps at 10A automatic fuse	42
max. no. of lamps at 16A automatic fuse	68
dimmable	Nein

Light Application Parameters

Luminous flux	4000 lm
Rated lamp luminous flux	4000 lm
Luminous flux	4000-4000 lm
Luminous flux in 90°-sector	4000 lm lm
Beam angle	360 °
Efficacy	133,33 lm/W
Total mains efficacy	133,33 lm/W
Color temperature	4000 K
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 6 sdcm

Service Life

Average life	50000 h
Mean service life	50000 h
No. switching cycles	100000
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤1.0%
Guarantee	5 years

Specification

Energylabel (G -> A)	E
Energylabel (E -> A++)	A++
Diameter	75 mm
Length	170 mm
Length	170 mm
Burning position	any

LED HPM-Retrofit

RL-HRL80 840/E27



Specification

Mercury content	0.0 mg
Material	Glass
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, single-ended
Base	E27
Colour	White

Notes on Operation

Degree of protection (IP)	IP65
Burning position	any
Mode of operation	CCG, 230V
Range of storage temperature	-20+80 °C
Ambient temperatures	-20 +60°C

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Type of color temperature	SINGLE_VALUE
EPREL ID number	878062

Notes

LED lamp for exchange with mercury lamps (HPM), non-dim, base E27. Operation with ballast (1:1 replacement) or without (= with 230V). No UV or IR.

 $\label{eq:please} \textit{Please, refer to} \ \underline{\textit{www.radium.de/recycling}} \ \textit{for notes on disposal of burned-out lamps as well as lamp breakage}.$

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht



E27 IEC/EN 60061-1 sheet 7004-21-9

Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.


LED HPM-Retrofit RL-HRL80 840/E27



Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit lamps 4000K



Besonderheiten





Allgemeine Hinweise

When replacing mercury vapor lamps HRL with LED lamps, we recommend replacement at the respective light point with operation at mains voltage directly (disconnect ballast, for lamps with article no. 426...), newer generations may also be replaced 1:1 (ballast remains in luminaire, lamps with article no. 43...) An ambient temperature of the lamp of 60 ° C inside the luminaire must not be exceeded. Outdoor use is permitted (IP65).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.