# **LED Strip operational gear**DRIVER FLAT 120W/24V IP20 RADIUM



Product Datasheet Date: 05.11.2025



## **General Data**

Artikel Nr.	OTNA3105
Bestellzeichen	DRIVER FLAT 120W/24V IP20 RADIUM
EAN-Faltschachtel	4003556010048
Versandeinheit in Stk.	40
EAN Umkarton (Versandeinheit)	4003556410046
Brutto-Gewicht Versandeinheit in kg	11.55
Länge Versandeinheit in m	0.45
Breite Versandeinheit in m	0.24
Höhe Versandeinheit in m	0.2
Product weight	255 g
Produktstatus	Aktiv

## **Electric Parameters**

Rated value output power max.	120.0 W	
Output power	0-120.0 W	
Power factor	>0,95	
Input voltage AC (range)	220-240 V	
Output Voltage	24 V	
Output voltage	24-24 V	
Surge voltage resistance (L - N)	2 kV	
Number of Channels	1	
Output current	0-5000 mA	
Supply frequency	50/60 Hz	

## **LED Strip operational gear**

DRIVER FLAT 120W/24V IP20 RADIUM



#### **Electric Parameters**

Suitable for DC-voltage (primary side)	Nein
max. no. of lamps at 16A automatic fuse	8
dimmable	Nein
Dimming with push-button	Nein

## **Service Life**

Service life	50000 h
Tc Temperature max.	90 °C

## **Specification**

Mean efficiency	>91 %
Length	190 mm
Height max.	22 mm
Width	65 mm
Material	Plastic
Model	Static

## **Notes on Operation**

Degree of protection (IP)	IP20	
Type of connection	spring clamp	
Ambient temperatures	-25+45	
Tc Temperature max.	90 °C	

## **Miscellaneous**

Similar products	OTNA3104, OTNA3106	

#### **Notes**

Compact constant voltage supply 24V for operation of LED modules, not dimmable, for indoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Besonderheiten



# LED Strip operational gear

DRIVER FLAT 120W/24V IP20 RADIUM



#### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.