

LED Star tubular shape, R7s

RL-TS125 DIM 827/R7S

Radium

Product Datasheet Date: 10.11.2026





E	16	2000	2700K	25 000h	Dimmbar	5 YEARS GUARANTEE

General Data

Artikel Nr.	43719744
Bestellzeichen	RL-TS 125 DIM 827/R7S
EAN-Faltschachtel	4008597197444
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4008597597442
Brutto-Gewicht Versandeinheit in kg	2.054
Länge Versandeinheit in m	0.159
Breite Versandeinheit in m	0.129
Höhe Versandeinheit in m	0.131
Product weight	95 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	16.0 W
Nominal power	16.0 W
Weighted energy consumption in 1000 hours	16 kWh
Lamp power	16.0-16.0 W
Power factor	≥ 0.9

LED Star tubular shape, R7s

RL-TS125 DIM 827/R7S

Radium

Electric Parameters

Power factor	0,9
Nominal voltage	220-240 V
Voltage type	AC
Nominal current	70-70 mA
Nominal current (mA)	70 mA
Inrush current	4,93 A
max. no. of lamps at 10A-B10 automatic fuse	15
max. no. of lamps at 16A-B16 automatic fuse	24
dimmable	Ja

Light Application Parameters

Luminous flux	2000 lm
Rated lamp luminous flux	2000 lm
Beam angle	300 °
Efficacy / Luminous efficiency	125 lm/W
Total mains efficacy	125 lm/W
Color temperature	2700 K
Color coordinate X	0.458
Color coordinate Y	0.410
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 6 sdcm

Service Life

Average life	25000 h
Mean service life	25000 h
No. switching cycles	[100000]
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	5 years

Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	E
Diameter	28 mm
Length max.	118 mm

LED Star tubular shape, R7s

RL-TS125 DIM 827/R7S

Radium

Specification

Length	118 mm
Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG1
Lamp shape	Tube, double-ended
Base	R7s
Colour	White
Housing colour	Other

Notes on Operation

IP Class (Room/Ceiling)	IP 20
Burning position	any
Mode of operation	230 V
Ambient temperatures	-20 … +40 °C
With movement sensor	Nein

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
Lighting technology	LED
Color tunable light source	Nein
Color rendering index R9	1
Color stability MacAdams EPREL	6
Displacement factor EPREL	0.70
Life factor EPREL	0.90
Lumen maintenance EPREL	0.70
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	541563

Miscellaneous

Similar products	43819828

Notes

LED tubular lamp for exchange with halogen lamps, warm white light, dimmable, base R7s. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

LED Star tubular shape, R7s
RL-TS125 DIM 827/R7S

Radium


Sockelübersicht




R7s
IEC/EN 60061-1
sheet 7004-92A-4

Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED-Retrofit-Lamps 2700K



daylight(D 65)

Besonderheiten









Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.