
High pressure sodium lamp RNP-T/LR 400W/S/230/E40



Product Datasheet Date: 05.11.2025















56500

2000K

36 000h Dimmbar

General Data

Artikel Nr.	34414856
Bestellzeichen	RNP-T/LR 400W/S/230/E40
EAN-Faltschachtel	4008597148569
Versandeinheit in Stk.	12
EAN Umkarton (Versandeinheit)	4008597448560
Brutto-Gewicht Versandeinheit in kg	2.408
Länge Versandeinheit in m	0.266
Breite Versandeinheit in m	0.216
Höhe Versandeinheit in m	0.342
Product weight	150 g
Produktstatus	Aktiv

Electric Parameters

Wattage	415.5 W
Lamp nominal wattage	400 W
Weighted energy consumption in 1000 hours	416 kWh
Lamp voltage	105 V
Mains voltage	230 V

High pressure sodium lamp RNP-T/LR 400W/S/230/E40



Electric Parameters

Ignition voltage	3.3 up to 5.0
Lamp's nominal current	4.5 A
Nominal choke current	4.6 A
Compensation capacitor for 50Hz operation	45 μF
Running up current max.	125%
Fuse	Daelay-action; min. double nominal current
dimmable	Ja
Controllable (in suitable circuit)	up to 50% (Run up at nominal power)

Light Application Parameters

Luminous flux	56500 lm	
Rated lamp luminous flux	56500 lm	
Efficacy	136 lm/W	
Total mains efficacy	126 lm/W	
Colour temperature	2000 K	
Color coordinate X	0,535	
Color coordinate Y	0.420	
Color rendering index	25	
Lumen maintenance at 2000h	0.98	
Lumen maintenance at 4000h	0.97	
Lumen maintenance at 6000h	0.96	
Lumen maintenance at 8000h	0.95	
Lumen maintenance at 12000h	0.94	
Lumen maintenance at 16000h	0.94	
Lumen maintenance at 20000h	0.94	

Service Life

Average life	36000 h	
B5 - Service life 5% failures	20000 h	
B10 - Service life 10% failures	24000 h	
Lamp survival factor at 2000h	0.99	
Lamp survival factor at 4000h	0.99	
Lamp survival factor at 6000h	[0.98]	
Lamp survival factor at 8000h	0.98	
Lamp survival factor at 12000h	0.97	
Lamp survival factor at 16000h	0.96	

High pressure sodium lamp

RNP-T/LR 400W/S/230/E40



Service Life

·

Specification

Energylabel (G -> A)	E
Diameter	47 mm
Length	285 mm
Total length max.	285 mm
Burning position	h180
Mercury content	24.0 mg
Lamp shape	Tube, single-ended
Model	Clear
Base	E40

Notes on Operation

Burning position	h180	

Information especially for EPREL

EPREL ID number	541469	

Miscellaneous

Similar products	32417735, 34419716

Notes

High pressure sodium lamp long run (4Y), tubular bulb clear, base E40. Operation with ballast and ignitor.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht



E27 IEC/EN 60061-1 sheet 7004-21-9

Spektrale Strahlungsverteilung

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing


High pressure sodium lamp

RNP-T/LR 400W/S/230/E40




time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K. Every discharge lamp type has got an individual spectral power distribution according to its chemical filling. From this result important properties light colour or colour rendering. Sodium vapour lamps are very economic, due to the yellow light RNP lamps have got a high luminous efficiency but only modest colour rendering.

After the lamp start a high pressure sodium lamp needs about 6-10 minutes time to reach its full luminous flux. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



RNP Standard/Super



daylight(D 65)

Besonderheiten





Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.