
# Halogen lamp double based

RJH-TSK 120W/230/C/XE/R7S



Product Datasheet Date: 05.11.2025













22

2245

2 000h

Dimmbar

### **General Data**

Artikel Nr.	22315972
Bestellzeichen	RJH-TSK 120W/230/C/XE/R7S
EAN-Faltschachtel	4008597159725
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4008597459726
Brutto-Gewicht Versandeinheit in kg	0.207
Länge Versandeinheit in m	0.09
Breite Versandeinheit in m	0.11
Höhe Versandeinheit in m	0.08
Product weight	6 g
Produktstatus	Aktiv

## **Electric Parameters**

Lamp power	120.0 W
Weighted energy consumption in 1000 hours	120 kWh
Lamp voltage	220-240 V
Mains voltage	230 V
dimmable	Ja

# Halogen lamp double based

RJH-TSK 120W/230/C/XE/R7S



## **Light Application Parameters**

Luminous flux	2245 lm
Rated lamp luminous flux	2245 lm
Efficacy	19 lm/W
Colour temperature	2900 K
Color rendering index	100

### **Service Life**

Average life	2000 h
No. switching cycles	10000

## **Specification**

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	12 mm
Length	81 mm
Total length max.	80.3 mm
Length	80.3 mm
Contact distance I	74.9 mm
Burning position	any
Mercury content	0.0 mg
Lamp shape	Tube, double-ended
Model	Clear
Base	R7s

## **Notes on Operation**

Burning position	any	

## Information especially for EPREL

Energylabel notice	current label, with EPREL registration
Lighting technology	HL
Directional or non-directional light	NDLS
EPREL ID number	566082

#### **Miscellaneous**

Similar products	22315971	

# Halogen lamp double based

RJH-TSK 120W/230/C/XE/R7S



#### **Notes**

Mains voltage halogen lamp clear, tubular shape, 230V mains, double ended, base R7s, dimmable steplessly

Please, refer to <a href="www.radium.de/recycling">www.radium.de/recycling</a> for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Sockelübersicht




R7s IEC/EN 60061-1 sheet 7004-92A-4

#### Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in effiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps



daylight(D 65)

#### Besonderheiten





#### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.