
RNP-E 70W/I/230/E27



Product Datasheet Date: 05.11.2025











2000K



24 000h

590

**General Data** 

5900

Artikel Nr.	34414712
Bestellzeichen	RNP-E 70W/I/230/E27
EAN-Faltschachtel	4008597147128
Versandeinheit in Stk.	24
EAN Umkarton (Versandeinheit)	4008597447129
Brutto-Gewicht Versandeinheit in kg	1.919
Länge Versandeinheit in m	0.36
Breite Versandeinheit in m	0.285
Höhe Versandeinheit in m	0.355
Product weight	50 g
Produktstatus	Aktiv

### **Electric Parameters**

Wattage	74.6 W
Lamp nominal wattage	70 W
Weighted energy consumption in 1000 hours	75 kWh
Lamp voltage	90 V
Mains voltage	220-240 V

RNP-E 70W/I/230/E27



### **Electric Parameters**

Ignition voltage	0.198	
Nominal current (A)	0.98 A	
Nominal choke current	1 A	
Compensation capacitor for 50Hz operation	12 μF	
Fuse	Daelay-action; min. double nominal current	
dimmable	Nein	

# **Light Application Parameters**

Luminous flux	5900 lm	
Rated lamp luminous flux	5900 lm	
Efficacy	79 lm/W	
Total mains efficacy	73 lm/W	
Colour temperature	2000 K	
Color coordinate X	0,535	
Color coordinate Y	0.420	
Color rendering index	< 25	
Lumen maintenance at 2000h	0.92	
Lumen maintenance at 4000h	0.86	
Lumen maintenance at 6000h	0.83	
Lumen maintenance at 8000h	0.82	
Lumen maintenance at 12000h	0.81	
Lumen maintenance at 16000h	0.81	
Lumen maintenance at 20000h	0.80	

### **Service Life**

Average life	24000 h	
B5 - Service life 5% failures	12000 h	
B10 - Service life 10% failures	14000 h	
Lamp survival factor at 2000h	0.98	
Lamp survival factor at 4000h	0.97	
Lamp survival factor at 6000h	0.97	
Lamp survival factor at 8000h	0.96	
Lamp survival factor at 12000h	0.95	
Lamp survival factor at 16000h	0.85	
Lamp survival factor at 20000h	0.70	

RNP-E 70W/I/230/E27



#### **Specification**

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	71 mm
Length	156 mm
Total length max.	156 mm
Burning position	h180
Mercury content	10.8 mg
Lamp shape	Ellipsoid
Model	Opal
Base	E27

#### **Notes on Operation**

Burning position	h180

## Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	541454

#### **Notes**

Standard high pressure sodium lamp, elliptical bulb coated, base E27, Operation with ballast, no ignitor required.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Sockelübersicht



E27 IEC/EN 60061-1 sheet 7004-21-9

#### Spektrale Strahlungsverteilung

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K.


Every discharge lamp type has got an individual spectral power distribution according to its chemical filling. From this result important properties light colour or colour rendering. Sodium vapour lamps are very economic, due to the yellow light RNP lamps have got a high luminous efficiency but only modest colour rendering.

After the lamp start a high pressure sodium lamp needs about 6-10 minutes time to reach its full luminous flux.


Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

RNP-E 70W/I/230/E27





RNP Standard/Super



daylight(D 65)

#### Besonderheiten





#### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.