
RJL 60W/12/SKY/IRC/GY6.35



Product Datasheet Date: 05.11.2025













1560

560 3000K

4 000h

General Data

Audit at Nie	00040450
Artikel Nr.	22319450
Bestellzeichen	RJL 60W/12/SKY/IRC/GY6.35
EAN-Faltschachtel	4008597194504
Versandeinheit in Stk.	40
EAN Umkarton (Versandeinheit)	4008597494505
Brutto-Gewicht Versandeinheit in kg	0.2
Länge Versandeinheit in m	0.144
Breite Versandeinheit in m	0.107
Höhe Versandeinheit in m	0.121
Product weight	2 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	60.0 W
Weighted energy consumption in 1000 hours	60 kWh
Nominal voltage	12 V
Lamp voltage	12-12 V
Nominal current	5000 mA

RJL 60W/12/SKY/IRC/GY6.35



Electric Parameters

Lamp's nominal current 5 A

Light Application Parameters

Luminous flux	1560 lm
Rated lamp luminous flux	1560 lm
Efficacy	26 lm/W
Colour temperature	3000 K
Color coordinate X	0,437
Color coordinate Y	0,404
Color rendering index	100

Service Life

Average life	4000 h
No. switching cycles	50000

Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	12 mm
Length	45 mm
Total length max.	44 mm
Burning position	any
Model	Clear
Base	GY6.35

Notes on Operation

Burning position any

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	533419

Miscellaneous

EU-date of phase-out	01.09.2023
EU Directive	SLR = (EU) 2019/2020

RJL 60W/12/SKY/IRC/GY6.35



Similar products 22320009

RJL 60W/12/SKY/IRC/GY6.35



Notes

IRC low voltage halogen pin base lamp, 12V operation with transformer, base GY6.35, stepless dim, 4000 h mean service life

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht




GY6.35 IEC/EN 60061-1 sheet 7004-59-6

Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in effiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps



daylight(D 65)

Besonderheiten



Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.