
RL-T8 36 FOOD 833/G13 EM



Product Datasheet Date: 05.11.2025











3300K





44.0

1100

100

50 000h

General Data

Artikel Nr.	43719799
Bestellzeichen	RL-T8 36 S FOOD 833/G13 EM
EAN-Faltschachtel	4008597197994
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597497995
Brutto-Gewicht Versandeinheit in kg	3.111
Länge Versandeinheit in m	1.352
Breite Versandeinheit in m	0.21
Höhe Versandeinheit in m	0.115
Product weight	213 g
Produktstatus	Aktiv

Electric Parameters

Wattage	11.6 W
Nominal power	11.6 W
Weighted energy consumption in 1000 hours	12 kWh
Lamp power	11.6-11.6 W
Power factor	> 0.9

RL-T8 36 FOOD 833/G13 EM



Electric Parameters

Nominal voltage	220-240 V
Voltage type	AC
Nominal current	56-56 mA
Nominal current (mA)	56 mA
Inrush current	7 A
max. no. of lamps at 10A automatic fuse	81
max. no. of lamps at 16A automatic fuse	129
dimmable	Nein

Light Application Parameters

Luminous flux	1100 lm
Rated lamp luminous flux	1100 lm
Beam angle	190 °
Efficacy	95 lm/W
Total mains efficacy	95 lm/W
Color temperature	3300 K
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 5 sdcm

Service Life

Average life	50000 h
Tc Temperature max.	65 °C
Mean service life	50000 h
Lifetime L70B50	50000 h
Tc max. with CCG or 230V AC	65 °C
No. switching cycles	200000
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	5 years

Specification

Diameter	26,7 mm
Length	1212 mm
Length	1200 mm
Burning position	any

RL-T8 36 FOOD 833/G13 EM



Specification

Mercury content	0.0 mg
Shatterproof	Ja
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, double-ended
Base	G13
Colour	White

Notes on Operation

Degree of protection (IP)	IP20	
Burning position	any	
Mode of operation	CCG, 230V	
Range of storage temperature	-20+80 °C	
Ambient temperatures	-20 +50 °C	
Tc Temperature max.	65 °C	
Tc max. with CCG or 230V AC	65 °C	

Information especially for EPREL

Lighting technology	LED	
Color tunable light source	Nein	
Color stability MacAdams EPREL	5	
Lumen maintenance EPREL	0,7	
EPREL ID number	730116	

Miscellaneous

Similar products	43719850	

Notes

T8 LED tube for food lighting, warm white light, glass bulb, non-dim, base G13. Please, note installation instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht



G13 IEC/EN 60061-1 sheet 7004-51-8

RL-T8 36 FOOD 833/G13 EM




Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit tubes for fluorescent lamps 3300K, particularly good color rendering in the red range



daylight(D 65)

Besonderheiten









Allgemeine Hinweise

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.