

Building-in aluminium profile for 1 LED-strip, Wing Profile SMALL

Length 5m

Product Datasheet Date: 10.11.2026





General Data

Artikel Nr.	TRPA2525
Bestellzeichen	PROFILE SMALL WING 25/13/B1C1 5M
EAN-Faltschachtel	4003556010659
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4003556410657
Brutto-Gewicht Versandeinheit in kg	13.35
Länge Versandeinheit in m	5.11
Breite Versandeinheit in m	0.07
Höhe Versandeinheit in m	0.053
Product weight	997 g
Produktstatus	Aktiv

Specification

Type of accessory/spare part	Profile
Length	5 m
Built-in width	17.3 mm
Product shape	Wing profile

Notes on Operation

Fitting Endcap	ZTPA2612, ZTPA2719, ZTPA4411
Fitting mounting clips or suspension	ZTPA2620, ZTPA2621, ZTPA4434, ZTPA4433

Building-in aluminium profile for 1 LED-strip, Wing Profile SMALL

Length 5m

Miscellaneous

Similar products	TRPA2515, TRPA2505, TRPA2535

Notes

High-quality, anodized aluminum installation profile for optimal cooling. It offers versatile mounting options and protects the LED strip.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Allgemeine Hinweise
The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.