



General Data

Artikel Nr.	OTDA4104
Bestellzeichen	DRIVER DALI 1CH 160W/24V IP20
EAN-Faltschachtel	4062172178006
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4062172178013
Brutto-Gewicht Versandeinheit in kg	7.918
Länge Versandeinheit in m	0.335
Breite Versandeinheit in m	0.268
Höhe Versandeinheit in m	0.167
Product weight	380 g
Produktstatus	● Inaktiv

Electric Parameters

Output voltage	24 V
Dimming with push-button	Nein

Specification

Model	Static
-------	--------

Notes on Operation

Degree of protection (IP)	IP20
---------------------------	------

Miscellaneous

LED driver DALI
DRIVER DALI 1CH 160W/24V IP20

Radium

Similar products

OTDA4100, OTDA4102

LED driver DALI

DRIVER DALI 1CH 160W/24V IP20

Radium

Notes

1 channel constant voltage supply 24V for up to 160W LED load, dimmable via DALI interface or touch button, for indoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Besonderheiten



Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.