
LED driver DALI

DRIVER DALI 1CH 80W/24V IP20

Radium

Product Datasheet Date: 11.11.2026



General Data

Artikel Nr.	OTDA4102
Bestellzeichen	DRIVER DALI 1CH 80W/24V IP20
EAN-Faltschachtel	4062172177986
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4062172177993
Brutto-Gewicht Versandeinheit in kg	3.998
Länge Versandeinheit in m	0.37
Breite Versandeinheit in m	0.17
Höhe Versandeinheit in m	0.113
Product weight	191 g
Produktstatus	Inaktiv

Electric Parameters

Output voltage	24 V
Dimming with push-button	Nein

Specification

Model	Static

Notes on Operation

Degree of protection (IP)	IP20
Protection class	II

LED driver DALI
DRIVER DALI 1CH 80W/24V IP20

Radium

Miscellaneous

Similar products	OTDA4100

Notes

1 channel constant voltage supply 24V for up to 80W LED load, dimmable via DALI interface or touch button, for indoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Besonderheiten



Allgemeine Hinweise
The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.