

DC Tube for external drivers
LED T5 NEO 35/49 840/G5

Radium

Product Datasheet Date: 10.11.2026





C | 4000K | 90 000h | Dimmbar

General Data

Artikel Nr.	43720835
Bestellzeichen	RL-T5 35/49 NEO 840/G5 DC
EAN-Faltschachtel	4008597208355
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597508356
Brutto-Gewicht Versandeinheit in kg	2.497
Länge Versandeinheit in m	1.52
Breite Versandeinheit in m	0.155
Höhe Versandeinheit in m	0.08
Product weight	172 g
Produktstatus	Aktiv

Electric Parameters

Wattage	23.4 W
Weighted energy consumption in 1000 hours	24 kWh
Lamp power	13.2-23.4 W
Power factor	1
Nominal voltage	66-66.9 V

DC Tube for external drivers
LED T5 NEO 35/49 840/G5

Radium

Electric Parameters

Voltage type	DC
Nominal current	200-350 mA
dimmable	Ja

Light Application Parameters

Luminous flux	4300 lm
Rated luminous flux according to IEC 62612	4300 lm
Luminous flux	2520-4300 lm
Lumen-Output mark	HE / HO
Beam angle	220 °
Efficacy / Luminous efficiency	184 lm/W
Total mains efficacy	170 lm/W
Color temperature	4000 K
Color coordinate X	0.3818
Color coordinate Y	0.3797
Color rendering index	> 80
Color Stability	≤ 5 sdcm

Service Life

Average life	90000 h
Tc Temperature max.	95 °C
Mean service life	90000 h
Life L70B10	90000 h
Life L80B10	60000 h
Min. number of switching cycles	20000
Guarantee	5 years

Specification

Energylabel (G -> A)	C
Diameter	17 mm
Tube diameter	15.7 mm
Length	1449 mm
Length	1449 mm
Burning position	any
Mercury content	0.0 mg
Shatterproof	Nein

DC Tube for external drivers
LED T5 NEO 35/49 840/G5

Radium

Specification

Lamp shape	Tube, double-ended
Base	G5
Material	Glass
Colour	White

Notes on Operation

IP Class (Room/Ceiling)	IP20
Burning position	any
Mode of operation	DC
Range of storage temperature	-20 ... +60°C
Ambient temperatures	-20 ... +45°C
Tc Temperature max.	95 °C
With movement sensor	Nein

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	NMLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	5
Displacement factor EPREL	1
Life factor EPREL	0.9
Lumen maintenance EPREL	0.93
EPREL ID number	1594010

Miscellaneous

Similar products	43720834, 43720836

Notes

T5 LED tube for external LED driver, replacement with fluorescent lamps, neutral white light color, glass bulb, dimmable, G5 base

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht
G5
IEC/EN 60061-1


DC Tube for external drivers
LED T5 NEO 35/49 840/G5

Radium


sheet 7004-52-5



Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED-NEO-Tubes 4000K, Replacements for fluorescent lamps



daylight(D 65)

Besonderheiten



Allgemeine Hinweise
Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.