
RL-PAR16 80 DIM 940/WFL



Product Datasheet Date: 05.11.2025



















8

8,3

575

4000K

25 000h

Dimmbar

General Data

Artikel Nr.	44020757
Bestellzeichen	RL-PAR16 80 DIM 940/WFL
EAN-Faltschachtel	4008597207570
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597507571
Brutto-Gewicht Versandeinheit in kg	0.693
Länge Versandeinheit in m	0.255
Breite Versandeinheit in m	0.107
Höhe Versandeinheit in m	0.072
Product weight	56 g
Produktstatus	Inaktiv

Electric Parameters

Wattage	8.3 W
Nominal power	8.3 W
Weighted energy consumption in 1000 hours	9 kWh
Lamp power	8.3-8.3 W
Power factor	0.7

RL-PAR16 80 DIM 940/WFL



Electric Parameters

Nominal voltage	220-240 V
Mains Voltage	220 - 240 V
Voltage type	AC
Nominal current	46-46 mA
Nominal current (mA)	46 mA
max. no. of lamps at 10A automatic fuse	117
max. no. of lamps at 16A automatic fuse	187
dimmable	Ja

Light Application Parameters

Luminous flux	575 lm	
Rated lamp luminous flux	575 lm	
Luminous flux	575-575 lm	_
Luminous intensity	840 cd	
Beam angle	36 °	
Efficacy	69 lm/W	
Total mains efficacy	69 lm/W	
Light colour	Neutral white	
Color temperature	4000 K	_
Color coordinate X	0,379	
Color coordinate Y	0,369	
Color rendering index	≥ 90	
Color rendering index nominal	90	
Color Stability	≤ 5 sdcm	

Service Life

Average life	25000 h	
Tc Temperature max.	105 °C	
Mean service life	25000 h	
No. switching cycles	[100000]	
Lamp survival factor at 6000h	≥ 0.90	
Early failure rate at 1000h	≤ 5.0 %	
Guarantee	5 years	

RL-PAR16 80 DIM 940/WFL



Specification

Energylabel (G -> A)	G
Diameter	50 mm
Length	52 mm
Length	52 mm
Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG1
Lamp shape	Reflector
Base	GU10
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	230 V
Ambient temperatures	-20 +40 °C
Tc Temperature max.	105 ℃

Information especially for EPREL

Lighting technology	LED	
Mains/Non mains connectable	MLS	
Directional or non-directional light	DLS	
Color tunable light source	Nein	
Type of color temperature	SINGLE_VALUE	
Color rendering index R9	40	
Color stability MacAdams EPREL	5	
Displacement factor EPREL	0,7	
Life factor EPREL	0,9	
Lumen maintenance EPREL	0,7	
Flicker	0.2	
Stroboscopic effect	0.4	
EPREL ID number	1569000	

Miscellaneous

Similar products	43820756, 43820086, 43919837, 43920152, 43922571, 43920771, 44020759,
	44020762

RL-PAR16 80 DIM 940/WFL



Notes

PAR16-LED for exchange with halogen lamps, neutral white light, glass bulb, dimmable, base GU10. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht




GU10 IEC/EN 60061-1 sheet 7004-121-1

Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED Retrofit reflector lamps 4000K



Besonderheiten







Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated

LED Star PAR16 RL-PAR16 80 DIM 940/WFL



with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.