
LED Essence Classic A, Filament
RL-A100 827/C/E27 FIL

Radium

Product Datasheet Date: 10.11.2026





W	lm		h	4 YEARS GUARANTEE
10,5	1521	2700K	15 000h	

General Data

Artikel Nr.	44120801
Bestellzeichen	RL-A100 827/C/E27 FIL
EAN-Faltschachtel	4008597208010
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597508011
Brutto-Gewicht Versandeinheit in kg	0.58
Länge Versandeinheit in m	0.31
Breite Versandeinheit in m	0.13
Höhe Versandeinheit in m	0.124
Product weight	34 g
Produktstatus	Aktiv

Electric Parameters

Wattage	10.5 W
Nominal power	10.5 W
Weighted energy consumption in 1000 hours	11 kWh
Lamp power	10.5 W
Power factor	> 0.5

LED Essence Classic A, Filament

RL-A100 827/C/E27 FIL

Radium

Electric Parameters

Power factor	0,5
Nominal voltage	220-240 V
Voltage type	AC
Nominal current	82 mA
Nominal current (mA)	82 mA
Inrush current	4.13 A
max. no. of lamps at 10A-B10 automatic fuse	83
max. no. of lamps at 16A-B16 automatic fuse	134
dimmable	Nein

Light Application Parameters

Luminous flux	1521 lm
Rated lamp luminous flux	1521 lm
Luminous flux	1521 lm
Beam angle	330 °
Efficacy / Luminous efficiency	145 lm/W
Total mains efficacy	145 lm/W
Color temperature	2700 K
Color coordinate X	0,458
Color coordinate Y	0,41
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 6 sdcm

Service Life

Average life	15000 h
Mean service life	15000
No. switching cycles	[100000]
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	4 years

Specification

Diameter	60 mm
Length	108 mm
Length	108 mm

LED Essence Classic A, Filament

RL-A100 827/C/E27 FIL

Radium

Specification

Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG1
Lamp shape	Pear-shape
Base	E27
Material	Glass
Colour	White

Notes on Operation

IP Class (Room/Ceiling)	IP 20
Burning position	any
Mode of operation	230 V
Ambient temperatures	-20 … +40 °C
With movement sensor	Nein

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	6
Displacement factor EPREL	0,5
Life factor EPREL	0.90
Lumen maintenance EPREL	0.9
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	1636780

Miscellaneous

Similar products	44020821, 43920799, 43920726

Notes

Standard LED lamp for exchange with incandescent lamps, clear glass bulb, non-dim, base E27. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

LED Essence Classic A, Filament

RL-A100 827/C/E27 FIL

Radium


Sockelübersicht




E27
IEC/EN 60061-1
sheet 7004-21-9

Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED-Retrofit-Lamps 2700K



daylight(D 65)

Besonderheiten







Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.