
# Connecting component Easy Connect POWER DISTRIBUTOR 6PORT P2 IP20 WHITE



Product Datasheet Date: 05.11.2025



## **General Data**

Artikel Nr.	FXZA4950
Bestellzeichen	POWER DISTRIBUTOR 6PORT P2 IP20 WHITE
EAN-Faltschachtel	4003556014442
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4003556414440
Brutto-Gewicht Versandeinheit in kg	0.285
Länge Versandeinheit in m	0.17
Breite Versandeinheit in m	0.09
Höhe Versandeinheit in m	0.13
Product weight	26 g
Produktstatus	Aktiv

# **Electric Parameters**

Voltage max.	36 V	
Current max. per channel	6 A	
Number of cores	2	

# **Specification**

Type of accessory/spare part	Other
Length	30 mm
Height	9 mm
Width	29 mm
Built-in width	29 mm
Colour	White

# **Connecting component Easy Connect**

POWER DISTRIBUTOR 6PORT P2 IP20 WHITE



# **Notes on Operation**

protection class (IP)	IP20
Ambient temperatures	-35 +60°C

### **Notes**

Six-way splitter for 2-pin power cables for professionally connecting six LED strips to one driver. (FXZA3995 connector not included)

Please, refer to <a href="www.radium.de/recycling">www.radium.de/recycling</a> for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains

(frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.