
# LED linear lamp, opal
RL-RAL1 35 DIM 922/O

Radium

Product Datasheet Date: 10.11.2026






F | 2200K | 25 000h | Dimmbar | 5 YEARS GUARANTEE

## General Data

| | |
|---|---|
| Artikel Nr. | 44014961 |
| Bestellzeichen | RL-RAL1 35 DIM 922/O |
| EAN-Faltschachtel | 4008597149610 |
| Versandeinheit in Stk. | 10 |
| EAN Umkarton (Versandeinheit) | 4008597449611 |
| Brutto-Gewicht Versandeinheit in kg | 1.153 |
| Länge Versandeinheit in m | 0.37 |
| Breite Versandeinheit in m | 0.215 |
| Höhe Versandeinheit in m | 0.148 |
| Product weight | 80 g |
| Produktstatus | Aktiv |

## Electric Parameters

| | |
|---|---|
| Wattage | 3.1 W |
| Weighted energy consumption in 1000 hours | 4 kWh |
| Lamp power | 3.1 W |
| Power factor | 0,83 |
| Nominal voltage | 220-240 V |

# LED linear lamp, opal
RL-RAL1 35 DIM 922/O

Radium

## Electric Parameters

| | |
|---|---|
| Voltage type | AC |
| Nominal current | 17 mA |
| Nominal current (mA) | 17 mA |
| dimmable | Ja |

## Light Application Parameters

| | |
|---|---|
| Luminous flux | 265 lm |
| Rated luminous flux according to IEC 62612 | 265 lm |
| Luminous flux | 265 lm |
| Beam angle | 200 ° |
| Efficacy / Luminous efficiency | 85 lm/W |
| Total mains efficacy | 85 lm/W |
| Color temperature | 2200 K |
| Color coordinate X | 0.502 |
| Color coordinate Y | 0.415 |
| Color rendering index | ≥ 90 |
| Color Stability | ≤ 6 sdcm |

## Service Life

| | |
|---|---|
| Average life | 25000 h |
| Mean service life | 25000 h |
| Min. number of switching cycles | 100000 |
| Guarantee | 5 years |

## Specification

| | |
|---|---|
| Energylabel (G -> A) | F |
| Diameter | 29 mm |
| Length | 300 mm |
| Length | 300 mm |
| Burning position | any |
| Lamp shape | Linear |
| Base | S14d |
| Material | Glass |
| Colour | White |

# LED linear lamp, opal
RL-RAL1 35 DIM 922/O

Radium

## Notes on Operation

| | |
|---|---|
| Degree of protection (IP) | IP20 |
| Burning position | any |
| Mode of operation | 230 V |
| Ambient temperatures | -20…+40 °C |
| With movement sensor | Nein |

## Information especially for EPREL

| | |
|---|---|
| Lighting technology | LED |
| Mains/Non mains connectable | MLS |
| Directional or non-directional light | NDLS |
| Color tunable light source | Nein |
| Type of color temperature | SINGLE_VALUE |
| Color stability MacAdams EPREL | 6 |
| Displacement factor EPREL | 0.85 |
| Life factor EPREL | 1 |
| Lumen maintenance EPREL | 0.96 |
| Flicker | 0.1 |
| Stroboscopic effect | 0.3 |
| EPREL ID number | 1997404 |

## Miscellaneous

| | |
|---|---|
| Similar products | 44014959 |

## Notes

RaLEDina, LED lamp for exchange with linear incandescent lamps, coated glass bulb, dimmable, base S14d. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

**Sockelübersicht**




S14d
IEC/EN 60061-1
sheet 7004-112-1


**Spektrale Strahlungsverteilung**
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

# LED linear lamp, opal
RL-RAL1 35 DIM 922/O

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




RaLEDina: LED retrofit for Linear incandescent lamp extra warm 2200K with best colour rendering CRI90




daylight(D 65)

**Besonderheiten**















**Allgemeine Hinweise**

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

**Sicherheitshinweise**

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

**All technical data without guarantee.**