

LED linear lamp, opal

RL-RAL1 60 DIM 922/O

Radium

Product Datasheet Date: 20.05.2026



F



2200K



25 000h



Dimmbar

General Data

Artikel Nr.	44014965
Bestellzeichen	RL-RAL1 60 DIM 922/O
EAN-Faltschachtel	4008597149658
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597449659
Brutto-Gewicht Versandeinheit in kg	1.739
Länge Versandeinheit in m	0.57
Breite Versandeinheit in m	0.215
Höhe Versandeinheit in m	0.148
Product weight	125 g
Produktstatus	● Aktiv

Electric Parameters

Wattage	4.9 W
Weighted energy consumption in 1000 hours	5 kWh
Lamp power	4.9 W
Nominal voltage	220-240 V
Voltage type	AC

Electric Parameters

Nominal current	29 mA
Nominal current (mA)	29 mA
dimnable	Ja

Light Application Parameters

Luminous flux	430 lm
Rated luminous flux according to IEC 62612	430 lm
Luminous flux	430 lm
Beam angle	200 °
Efficacy	88 lm/W
Total mains efficacy	88 lm/W
Color temperature	2200 K
Color coordinate X	0.502
Color coordinate Y	0.415
Color rendering index	≥ 90
Color Stability	≤ 6 sdcn

Service Life

Average life	25000 h
Mean service life	25000 h
Min. number of switching cycles	100000

Specification

Energylabel (G -> A)	F
Diameter	29 mm
Length	500 mm
Length	500 mm
Burning position	any
Material	Glass
Lamp shape	Linear
Base	S14d
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	230 V

Notes on Operation

Ambient temperatures	-20...+40 °C
With movement sensor	Nein

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	6
Life factor EPREL	1
Lumen maintenance EPREL	0.93
EPREL ID number	1997413

Miscellaneous

Similar products	44014963
------------------	----------

Notes

RaLEDina, LED lamp for exchange with linear incandescent lamps, coated glass bulb, dimmable, base S14d. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Socketübersicht



S14d
IEC/EN 60061-1
sheet 7004-112-1

Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.



The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

LED linear lamp, opal

RL-RAL1 60 DIM 922/O

Radium



RaLEDina: LED retrofit for Linear incandescent lamp extra warm 2200K with best colour rendering CRI90 daylight(D 65)

Besonderheiten



Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as that of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.