
# **LED linear lamp, opal** RL-RAL2 120 DIM 922/O



Product Datasheet Date: 05.11.2025















840

2200K

25 000h

#### **General Data**

Artikel Nr.	44014967
Bestellzeichen	RL-RAL2 120 DIM 922/O
EAN-Faltschachtel	4008597149672
Versandeinheit in Stk.	5
EAN Umkarton (Versandeinheit)	4008597449673
Brutto-Gewicht Versandeinheit in kg	2.303
Länge Versandeinheit in m	1.059
Breite Versandeinheit in m	0.278
Höhe Versandeinheit in m	0.085
Product weight	210 g
Produktstatus	Aktiv

#### **Electric Parameters**

Wattage	9.7 W
Weighted energy consumption in 1000 hours	10 kWh
Lamp power	9.7 W
Nominal voltage	220-240 V
Voltage type	AC

### LED linear lamp, opal

RL-RAL2 120 DIM 922/O



#### **Electric Parameters**

Nominal current	58 mA
Nominal current (mA)	58 mA

#### **Light Application Parameters**

Luminous flux	840 lm
Rated lamp luminous flux	840 lm
Luminous flux	840 lm
Beam angle	200 °
Efficacy	86 lm/W
Total mains efficacy	86 lm/W
Color temperature	2200 K
Color coordinate X	0.502
Color coordinate Y	0.415
Color rendering index	≥ 90
Color Stability	≤ 6 sdcm

#### **Service Life**

Average life	25000 h
Mean service life	25000 h
Min. number of switching cycles	100000
Guarantee	5 years

#### **Specification**

Energylabel (G -> A)	F
Diameter	29 mm
Length	1000 mm
Length	1000 mm
Burning position	any
Material	Glass
Lamp shape	Linear
Base	S14s
Colour	White

#### **Notes on Operation**

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	230 V

## LED linear lamp, opal

RL-RAL2 120 DIM 922/O



#### **Notes on Operation**

Ambient temperatures	-20+40 °C
7 Joint 10 por atta. 10	20

#### Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	6
Displacement factor EPREL	0.74
Life factor EPREL	1
Lumen maintenance EPREL	0.96
Flicker	0.2
Stroboscopic effect	0.7
EPREL ID number	1997416

#### **Miscellaneous**

Similar products	44014966	

#### **Notes**

RaLEDina, LED lamp for exchange with linear incandescent lamps, coated glass bulb, dimmable, base S14s. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Sockelübersicht



S14s IEC/EN 60061-1 sheet 7004-112-1

#### Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.


White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

## **LED linear lamp, opal** RL-RAL2 120 DIM 922/O





RaLEDina: LED retrofit for Linear incandescent lamp extra warm 2200K with best colour rendering CRI90



daylight(D 65)

#### Besonderheiten









#### Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

#### Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.