


LED EssenceDuo/E - Retrofit f. Ralux Duo/E
RL-DUO/E18 840/G24Q-2 HF

Radium

Product Datasheet Date: 01.04.2026





F



7



4000K



30 000h



General Data

Artikel Nr.	43620629
Bestellzeichen	RL-DUO/E18 840/G24Q-2 HF
EAN-Faltschachtel	4008597206290
Versandereinheit in Stk.	10
EAN Umkarton (Versandereinheit)	4008597406294
Brutto-Gewicht Versandereinheit in kg	0.795
Länge Versandereinheit in m	0.218
Breite Versandereinheit in m	0.092
Höhe Versandereinheit in m	0.171
Product weight	62 g
Produktstatus	Aktiv

Electric Parameters

Wattage	7.0 W
Nominal power	7.0 W
Weighted energy consumption in 1000 hours	7 kWh
Lamp power	7.0 W
Nominal voltage	30-70 V

Electric Parameters

Voltage type	AC
Nominal current	45 mA
Nominal current (mA)	45 mA
Inrush current	15 A
max. no. of lamps at 10A automatic fuse	182
max. no. of lamps at 16A automatic fuse	290
dimnable	Nein

Light Application Parameters

Luminous flux	660 lm
Rated luminous flux according to IEC 62612	660 lm
Luminous flux	660 lm
Beam angle	280 °
Efficacy	94 lm/W
Total mains efficacy	87 lm/W
Color temperature	4000 K
Color coordinate X	0.382
Color coordinate Y	0.380
Color rendering index	≥ 80
Color Stability	≤ 5 sdc _m

Service Life

Average life	30000 h
Mean service life	30000
Lifetime L70B50	30000 h
Min. number of switching cycles	20000
Guarantee	3 years

Specification

Energylabel (G -> A)	F
Diameter	34 mm
Length	146 mm
Length	146 mm
Burning position	any
Material	Glass
Photobiological safety according to EN 62471	RG0

LED EssenceDuo/E - Retrofit f. Ralux Duo/E

RL-DUO/E18 840/G24Q-2 HF

Radium

Specification

Lamp shape	Tube, single-ended
Base	G24q-1
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	ECG
Ambient temperatures	-20 ... +45 °C
With movement sensor	Nein

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	NMLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	5
Displacement factor EPREL	0,9
Life factor EPREL	0.9
Lumen maintenance EPREL	0.958
Flicker	1.0
EPREL ID number	2214101

Miscellaneous

Similar products	43520623, 43520622
------------------	--------------------

Notes

LED compact lamp for replacement with Ralux Duo, neutral white light, glass bulb, not dimmable, fits in lamp holder for base G24q only.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


Sockelübersicht

G24q
IEC/EN 60061-1
sheet 7004-78-5

LED EssenceDuo/E - Retrofit f. Ralux Duo/E

RL-DUO/E18 840/G24Q-2 HF

Radium




Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED retrofit lamps 4000K



daylight(D 65)

Besonderheiten



Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.