
RL-MR16 50 DIM 927/36°/GU5.3



Product Datasheet Date: 05.11.2025















G

6.8

2700K

25 000h

General Data

Artikel Nr.	44125233
Bestellzeichen	RL-MR16 50 DIM 927/36°/GU5.3
EAN-Faltschachtel	4008597252334
Versandeinheit in Stk.	10
EAN Umkarton (Versandeinheit)	4008597452338
Brutto-Gewicht Versandeinheit in kg	0.57
Länge Versandeinheit in m	0.255
Breite Versandeinheit in m	0.107
Höhe Versandeinheit in m	0.072
Product weight	42 g
Produktstatus	Aktiv

Electric Parameters

Wattage	6.8 W
Nominal power	6.8 W
Weighted energy consumption in 1000 hours	7 kWh
Nominal voltage	11.5-12 V
Voltage type	AC

RL-MR16 50 DIM 927/36°/GU5.3



Electric Parameters

Nominal current	650 mA
Inrush current	< 20 A

Light Application Parameters

Luminous flux	621 lm
Rated luminous flux according to IEC 62612	621 lm
Luminous flux	621 lm
Luminous intensity	1100 cd
Beam angle	36 °
Efficacy	91 lm/W
Total mains efficacy	91 lm/W
Color temperature	2700 K
Color coordinate X	0.463
Color coordinate Y	0.403
Color rendering index	≥ 90
Color Stability	≤ 6 sdcm

Service Life

Average life	25000 h	
Mean service life	25000 h	
Min. number of switching cycles	100000	
Guarantee	5 years	

Specification

50 mm 45 mm
45 mm
44 mm
any
Glass
RG0
Reflector
GU5.3
F

RL-MR16 50 DIM 927/36°/GU5.3



Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	LV transformer
Ambient temperatures	-20 +40 °C

Information especially for EPREL

Lighting technology	LED	
Directional or non-directional light	DLS	
Color tunable light source	Nein	
Type of color temperature	SINGLE_VALUE	
Color rendering index R9	45	
Color stability MacAdams EPREL	6	
Displacement factor EPREL	0.70	
Lumen maintenance EPREL	0.93	
Flicker	1.0	
Stroboscopic effect	0.4	
EPREL ID number	2386002	

Notes

MR16-LED, exchange with 12V halogen lamps, warm white light, glass bulb, dimmable, base GU5,3. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Sockelübersicht



GU5.3 IEC/EN 60061-1 sheet 7004-109-2

Spektrale Strahlungsverteilung


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

RL-MR16 50 DIM 927/36°/GU5.3





daylight(D 65)

Besonderheiten





Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.