
Surface-mount aluminium profile for 2 LED-strips

PROFILE MEDIUM U 27/25.9/B2C2 0.98M

Radium

Product Datasheet Date: 11.11.2026





General Data

Artikel Nr.	TRPA2540
Bestellzeichen	PROFILE MEDIUM U 27/25.9/B2C2 0.98M
EAN-Faltschachtel	4003556014602
Versandeinheit in Stk.	4
EAN Umkarton (Versandeinheit)	4003556408098
Brutto-Gewicht Versandeinheit in kg	1.416
Länge Versandeinheit in m	1.11
Breite Versandeinheit in m	0.07
Höhe Versandeinheit in m	0.053
Product weight	305 g
Produktstatus	Aktiv

Specification

Type of accessory/spare part	Profile
Length max.	980 mm
Length	0.98 m
Height	25,9 mm
Width	27 mm
Internal width	22.2 mm
no. of LED stripes in profile	2
Product shape	U profile
Material	Aluminium

Surface-mount aluminium profile for 2 LED-strips

PROFILE MEDIUM U 27/25.9/B2C2 0.98M

Radium

Notes on Operation

Mounting type	Surface mounted
Fitting Endcap	ZTPA2614, ZTPA2617, ZTPA4960, ZTPA3192, ZTPA3196, ZTPA4963
Fitting Cover	ZTPA2591, ZTPA2561
Fitting mounting clips or suspension	ZTPA2622, ZTPA2623, ZTPA3020, ZTPA3022

Miscellaneous

Similar products	TRPA2551, TRPA2561

Notes

High quality, anodized aluminum profile for optimal cooling. It offers versatile mounting options and space for up to two LED strips.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Allgemeine Hinweise
The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.