

2000

General Data

Artikel Nr.	32317007
Bestellzeichen	HTC 2000-329
EAN-Faltschachtel	4008597170072
Versandeinheit in Stk.	25
EAN Umkarton (Versandeinheit)	4008597470073
Brutto-Gewicht Versandeinheit in kg	2.438
Länge Versandeinheit in m	0.26
Breite Versandeinheit in m	0.25
Höhe Versandeinheit in m	0.26
Produktstatus	● Aktiv

Electric Parameters

Lamp power	2,000.0 W
Nominal power	2,000.0 W
Lamp voltage	250 V
Ignition voltage	4,0 - 5,0
Lamp's nominal current	9 A
Compensation capacitor for 50Hz operation	37 μ F

Light Application Parameters

Type of UV radiation	UV-A
----------------------	------

Specification

Diameter	28 mm
Tube diameter	28 mm
Length	174 mm
Total length max.	175 mm
Contact distance I	72 mm
radiator length (glass)	103 mm
Burning position	Random
Lamp shape	Tube, double-ended
Base	K10s

Notes on Operation

Burning position	Random
Generating ozone	Nein
Suitable for air disinfection	Nein
Suitable for water disinfection	Nein

Notes


High-pressure UV lamp, for use only in enclosed fixtures and with control gear. Observe safety instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Spektrale Strahlungsverteilung

Spektrale Strahlungsverteilung / spectral radiation distribution



Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or

High Pressure UV Lamps HTC

HTC 2000-329

Radium

even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.