

# LED Star Tube T8 UO

RL-T8 58 SP UO 865/G13 EM

# Radium

Product Datasheet Date: 20.05.2026



B



6500K



75 000h



## General Data

Artikel Nr.	43825055
Bestellzeichen	RL-T8 58 SP UO 865/G13 EM
EAN-Faltschachtel	4008597250552
Versandeinheit in Stk.	20
EAN Umkarton (Versandeinheit)	4008597450556
Brutto-Gewicht Versandeinheit in kg	6.73
Länge Versandeinheit in m	1.585
Breite Versandeinheit in m	0.185
Höhe Versandeinheit in m	0.14
Product weight	220 g
Produktstatus	<span style="color: green;">●</span> Aktiv

## Electric Parameters

Wattage	22.2 W
Weighted energy consumption in 1000 hours	23 kWh
Lamp power	22.2 W
Nominal voltage	220-240 V
Voltage type	AC

## Electric Parameters

Nominal current	134 mA
Nominal current (mA)	134 mA
Inrush current	12.8 A
max. no. of lamps at 10A-B10 automatic fuse	8
max. no. of lamps at 16A-B16 automatic fuse	12
dimnable	Nein

## Light Application Parameters

Luminous flux	4110 lm
Rated luminous flux according to IEC 62612	4110 lm
Luminous flux	4110 lm
Lumen-Output mark	UO
Beam angle	180 °
Efficacy	185 lm/W
Total mains efficacy	185 lm/W
Color temperature	6500 K
Color coordinate X	0.312
Color coordinate Y	0.328
Colour rendering index CRI	80-89
Color Stability	≤ 6 sdc <sub>m</sub>

## Service Life

Average life	75000 h
Min. number of switching cycles	20000
Guarantee	5 years

## Specification

Energylabel (G -> A)	B
Diameter	28 mm
Tube diameter	26 mm
Length max.	1500 mm
Length	1500 mm
Burning position	any
Material	Glass
Shatterproof	Ja
Photobiological safety according to EN 62471	RG0

## Specification

Lamp shape	Tube, double-ended
Base	G13
Colour	White

## Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	CCG, 230V
Ambient temperatures	-20 ... +50°C
With movement sensor	Nein

## Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	6
Displacement factor EPREL	0,9
Life factor EPREL	0.9
Lumen maintenance EPREL	0.99
Stroboscopic effect	0.4
EPREL ID number	2596410

## Notes

T8 tubular LED lamp for exchange with fluorescent lamps, daylight, glass bulb, non-dim, base G13. Please, note installation instructions!

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Sockelübersicht



G13  
IEC/EN 60061-1  
sheet 7004-51-8

### Spektrale Strahlungsverteilung

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

# LED Star Tube T8 UO

RL-T8 58 SP UO 865/G13 EM

# Radium

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



daylight(D 65)

## Besonderheiten



## Allgemeine Hinweise

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the respective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

## Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.