
LED Star PAR30
75 DIM 927/36°/E27

Radium

Product Datasheet Date: 10.11.2026





G | 2700K | 25 000h | Dimmbar | 5 YEARS GUARANTEE

General Data

Artikel Nr.	43820928
Bestellzeichen	RL-PAR30 75 DIM 927/36°/E27
EAN-Faltschachtel	4008597209284
Versandeinheit in Stk.	12
EAN Umkarton (Versandeinheit)	4008597409288
Brutto-Gewicht Versandeinheit in kg	2.545
Länge Versandeinheit in m	0.428
Breite Versandeinheit in m	0.326
Höhe Versandeinheit in m	0.18
Product weight	140 g
Produktstatus	Aktiv

Electric Parameters

Wattage	10.0 W
Weighted energy consumption in 1000 hours	10 kWh
Lamp power	10.0 W
Power factor	0.5
Nominal voltage	220-240 V

LED Star PAR30
75 DIM 927/36°/E27

Radium

Electric Parameters

Voltage type	AC
Nominal current	55 mA
Nominal current (mA)	55 mA
dimmable	Ja

Light Application Parameters

Rated luminous flux according to IEC 62612	633 lm
Luminous flux	633 lm
Beam angle	36 °
Luminous intensity	1500 cd
Efficacy / Luminous efficiency	74 lm/W
Total mains efficacy	74 lm/W
Color temperature	2700 K
Color coordinate X	0.458
Color coordinate Y	0.410
Colour rendering index CRI	80-89
Color Stability	≤ 6 sdcm

Service Life

Average life	25000 h
Mean service life	25000 h
Min. number of switching cycles	20000
Guarantee	5 years

Specification

Energylabel (G -> A)	G
Diameter	95 mm
Length	93 mm
Length	93 mm
Burning position	any
Photobiological safety according to EN 62471	RG1
Lamp shape	Reflector
Base	E27
Colour	White

LED Star PAR30
75 DIM 927/36°/E27

Radium

Notes on Operation

IP Class (Room/Ceiling)	IP20
Burning position	any
Ambient temperatures	-20 … +40 °C
With movement sensor	Nein

Information especially for EPREL

Lighting technology	LED
Directional or non-directional light	DLS
Color tunable light source	Nein
Type of color temperature	SINGLE_VALUE
Displacement factor EPREL	0,5
Life factor EPREL	0.9
Lumen maintenance EPREL	0.96
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	2608469

Notes

PAR30 LED for exchange with 230V halogen reflector lamps, warm white light, 36° beam angle, dimmable, glass bulb, base E27.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


Sockelübersicht




E27
IEC/EN 60061-1
sheet 7004-21-9

Spektrale Strahlungsverteilung
As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

LED Star PAR30
75 DIM 927/36°/E27



LED-Retrofit-Lamps 2700K



daylight(D 65)

Besonderheiten







Allgemeine Hinweise

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Sicherheitshinweise

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.