


High pressure sodium lamp

RNP-E 50W/I/230/E27

Radium

Product Datasheet Date: 31.01.2026



A



G



3600



2000K



24 000h

General Data

Article No.	34418915
Code	RNP-E 50W/I/230/E27
Product EAN	4008597189159
Box quantity (pcs.)	24
EAN Box	4008597489150
Gross weight of box in kg	2.381
Length of box in m	0.358
Width of box in m	0.283
Height of box in m	0.353
Product weight	55 g
Product status	● Inactive

Electric Parameters

Wattage	50.0 W
Lamp nominal wattage	50 W
Weighted energy consumption in 1000 hours	55 kWh
Lamp voltage	90 V
Mains voltage	230 V

High pressure sodium lamp

RNP-E 50W/I/230/E27

Radium

Electric Parameters

Lamp's nominal current	0.8 A
Nominal choke current	0.8 A
Compensation capacitor for 50Hz operation	10 µF
Running up current max.	125%
Fuse	Delay-action; min. double nominal current
dimmable	No

Light Application Parameters

Luminous flux	3600 lm
Rated lamp luminous flux	3600 lm
Efficacy	72 lm/W
Total mains efficacy	72 lm/W
Colour temperature	2000 K
Color rendering index	25
Lumen maintenance at 2000h	0.89
Lumen maintenance at 4000h	0.85
Lumen maintenance at 6000h	0.83
Lumen maintenance at 8000h	0.82
Lumen maintenance at 12000h	0.81
Lumen maintenance at 16000h	0.79
Lumen maintenance at 20000h	0.75

Service Life

Average life	24000 h
B5 - Service life 5% failures	9000 h
B10 - Service life 10% failures	12000 h
Lamp survival factor at 2000h	0.99
Lamp survival factor at 4000h	0.98
Lamp survival factor at 6000h	0.98
Lamp survival factor at 8000h	0.96
Lamp survival factor at 12000h	0.90
Lamp survival factor at 16000h	0.83
Lamp survival factor at 20000h	0.70

High pressure sodium lamp

RNP-E 50W/I/230/E27

Radium

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	A
Diameter	71 mm
Length	156 mm
Total length max.	156 mm
Burning position	hs30
Mercury content	19.0 mg
Lamp shape	Ellipsoid
Model	Opal
Base	E27

Notes on Operation

Burning position	hs30
------------------	------

Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
EPREL ID number	869022

Miscellaneous

EU Directive	TIM
--------------	-----

Notes

Standard high pressure sodium lamp, elliptical bulb coated, base E27, Operation with ballast, no ignitor required.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optional field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base



E27
IEC/EN 60061-1
sheet 7004-21-9

Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K. Every discharge lamp type has got an individual spectral power distribution according to its chemical filling. From this result important properties light

High pressure sodium lamp


RNP-E 50W/I/230/E27

Radium


colour or colour rendering. Sodium vapour lamps are very economic, due to the yellow light RNP lamps have got a high luminous efficiency but only modest colour rendering.

After the lamp start a high pressure sodium lamp needs about 6-10 minutes time to reach its full luminous flux.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




RNP Standard/Super



daylight(D 65)

Circuit diagram(s)



Standard circuit HID with internal ignitor

Key:

L. = lamp

VG = ballast electromagnetic (KVG/VVG)

P = phase

N = zero potential

K = p. f. correction capacitor

The required control gear (here ballast only) for the lamps operation is usually mounted in the suitable luminaire in an appropriate electric circuit. Changes of any kind are to be conducted by qualified and specialised staff, only. Thus, this circuit example is to be understood merely as a technical background information for interested users.

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.