


Low voltage halogen dichroic lamp

RJLS 20W/12/MEGA/WFL/GU4

Radium

Product Datasheet Date: 16.02.2026



B



G



220



3000K



4 000h



Dimmable

General Data

Article No.	22312452
Code	RJLS 20W/12/MEGA/WFL/GU4
Product EAN	4008597124525
Box quantity (pcs.)	10
EAN Box	4008597424526
Gross weight of box in kg	0.21
Length of box in m	0.176
Width of box in m	0.108
Height of box in m	0.053
Product weight	17 g
Product status	● Inactive

Electric Parameters

Wattage	20.0 W
Lamp nominal wattage	20 W
Weighted energy consumption in 1000 hours	22 kWh
Power factor	1.00
Lamp voltage	12-12 V

Electric Parameters

Mains voltage	12 V
Nominal current (A)	1.67 A
dimmable	Yes

Light Application Parameters

Rated lamp luminous flux	220 lm
Luminous flux in 90°-sector	220 lm
Luminous intensity	700 cd
Beam angle	36 °
Efficacy	11 lm/W
Colour temperature	3000 K
Color rendering index	100

Service Life

Average life	4000 h
No. switching cycles	100000

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	B
Diameter	35 mm
Length	40 mm
Total length max.	40 mm
Burning position	any
Mercury content	0.0 mg
Design	Wide Flood
Base	GU4
Colour	Other

Notes on Operation

Burning position	any
------------------	-----

Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
EPREL ID number	588329

Low voltage halogen dichroic lamp

RJLS 20W/12/MEGA/WFL/GU4

Radium

Miscellaneous

EU-date of phase-out

01.09.2021

EU Directive

SLR = (EU) 2019/2020

Notes

Low voltage halogen reflector lamp MR11 with front screen, 12V operation with transformer, base GU4, stepless dim, 4000 h mean service life

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base




GU4
IEC/EN 60061-1
sheet 7004-108-2

Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/km) per 10nm.




light of incandescent lamps



daylight(D 65)

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Low voltage halogen dichroic lamp
RJLS 20W/12/MEGA/WFL/GU4

Radium

All technical data without guarantee.