



General Data

Article No.	LMCSC43
Code	BCU 0-10V
Product EAN	4003556000780
Box quantitiy (pcs.)	100
EAN Box	4003556400788
Gross weight of box in kg	6.4
Length of box in m	0.46
Width of box in m	0.24
Height of box in m	0.25
Product weight	47 g
Product status	<div></div> Inactive

Electric Parameters

Standby consumption	1.1 W
max. output power relay contact	100.0 W
Inrush current	12 A
Period of inrush current	8 ms
Mains frequency	50 Hz
Dimming interface	1-10 V

Specification

Length	56.5 mm
Height max.	22 mm
Height	22.3 mm

## Specification

Width	35.8 mm
Model	Controller unit

## Notes on Operation

protection class (IP)	IP20
max. relative air humidity	80 %

## Information especially for EPREL

Standby consumption	1.1 W
---------------------	-------

## Miscellaneous

Similar products	LMBA0024, LMBA0025, LMBA0026
------------------	------------------------------

## Notes

Small light control unit for switching, dimming and colour setting (0-10V), installation via APP, retrieval also by switch.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Special features



### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.