


# LED Star LED-RetroFit AR111

RL-AR111 75 DIM 11.5W/12/FL/930/G53

# Radium

Product Datasheet Date: 20.04.2026



A



G



11,5



800



3000K



40 000h



Dimmable



5 YEARS GUARANTEE

## General Data

Article No.	43519342
Code	RL-AR111 75 DIM 930/FL
Product EAN	4008597193422
Box quantity (pcs.)	6
EAN Box	4008597493423
Gross weight of box in kg	1.314
Length of box in m	0.238
Width of box in m	0.208
Height of box in m	0.123
Product weight	160 g
Product status	<span style="color: red;">●</span> Inactive

## Electric Parameters

Wattage	11.5 W
Nominal power	11.5 W
Weighted energy consumption in 1000 hours	13 kWh
Lamp power	11.5-11.5 W
Power factor	> 0.70

## Electric Parameters

Nominal voltage	12-12 V
Voltage type	AC
Nominal current	1650-1650 mA
Nominal current (mA)	1100 mA
max. no. of lamps at 10A automatic fuse	4
max. no. of lamps at 16A automatic fuse	6
dimnable	Yes

## Light Application Parameters

Luminous flux	800 lm
Rated lamp luminous flux	800 lm
Luminous flux in 90°-sector	800 lm lm
Luminous flux in 120°-sector	800 lm lm
Luminous intensity	2000 cd
Beam angle	24 °
Efficacy	69 lm/W
Total mains efficacy	69 lm/W
Color temperature	3000 K
Color rendering index	≥ 90
Color rendering index nominal	90-100
Color Stability	≤ 6 sdcn

## Service Life

Average life	40000 h
Mean service life	40000 h
No. switching cycles	[100000]
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	5 years

## Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	A
Diameter	110,7 mm
Length max.	62 mm mm

## Specification

Length	62 mm
Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG0
Lamp shape	Reflector
Base	G53
Colour	White

## Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	LV transformer
Ambient temperatures	-20...+40 °C
With movement sensor	No

## Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Mains/Non mains connectable	NMLS
Directional or non-directional light	DLS
Color tunable light source	No
Type of color temperature	SINGLE_VALUE
Flicker	1.0
EPREL ID number	875164

## Notes

AR111-LED for exchange with 12V halogen lamps, warm white light, 24°, dimmable, base G53. LED light does not contain UV or IR radiation.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Base



G53  
IEC/EN 60061-1  
sheet 7004-134-1

### Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

# LED Star LED-RetroFit AR111


RL-AR111 75 DIM 11.5W/12/FL/930/G53

# Radium

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED Retrofit retrofit lamps 3000K



daylight(D 65)

## Special features



## General notes

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as that of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

## Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.