

Low voltage halogen pin base lamp

RJL 10W/12/SKY/G4

Radium

Product Datasheet Date: 26.06.2026



G



130



2800K



2 000h

General Data

Article No.	22320004
Code	RJL 10W/12/SKY/G4
Product EAN	4008597200045
Box quantity (pcs.)	40
EAN Box	4008597600043
Gross weight of box in kg	0.165
Length of box in m	0.144
Width of box in m	0.107
Height of box in m	0.121
Product weight	1 g
Product status	● Inactive

Electric Parameters

Wattage	10.0 W
Weighted energy consumption in 1000 hours	10 kWh
Nominal voltage	12 V
Lamp voltage	12-12 V
Nominal current	833 mA

Low voltage halogen pin base lamp

RJL 10W/12/SKY/G4

Radium

Light Application Parameters

Luminous flux	130 lm
Rated lamp luminous flux	130 lm
Efficacy / Luminous efficiency	13 lm/W
Colour temperature	3000 K
Color coordinate X	0,452
Color coordinate Y	0,409

Service Life

Average life	2000 h
No. switching cycles	50000

Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	10 mm
Total length max.	33 mm
Model	Clear
Base	G4

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	541049

Miscellaneous

EU-date of phase-out	01.09.2023
Similar products	43819832

Notes

Standard low voltage halogen pin base lamp, 12V operation with transformer, base G4, stepless dim, 2000 h mean service life

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base

G4
IEC/EN 60061-1
sheet 7004-72-3

Low voltage halogen pin base lamp

RJL 10W/12/SKY/G4

Radium




Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps



daylight(D 65)

General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.