


Compact fluorescent lamp Ralux® Duo

RX-D 10W/830/G24D

Radium

Product Datasheet Date: 29.10.2025





G



600



3000K



10 000h

General Data

Article No.	31319825
Code	RX-D 10W/830/G24D
Product EAN	4008597198250
Box quantitiy (pcs.)	10
EAN Box	4008597498251
Gross weight of box in kg	0.434
Length of box in m	0.186
Width of box in m	0.081
Height of box in m	0.132
Product weight	31 g
Product status	 Inactive

Electric Parameters

Wattage	10.7 W
Lamp nominal wattage	10 W
Weighted energy consumption in 1000 hours	11 kWh
Lamp voltage	64 V
Mains voltage	230 V

Electric Parameters

Nominal current (mA)	190 mA
Compensation capacitor for 50Hz operation	2.2 µF
dimmable	No

Light Application Parameters

Luminous flux	600 lm
Rated lamp luminous flux	600 lm
max. luminous flux at	25 °C
Efficacy	56 lm/W
Light colour	warm white
Code of light color	830
Colour temperature	3000 K
Color coordinate X	0,44
Color coordinate Y	0,403
Color rendering index	? 80
Mean luminance	4
Lumen maintenance at 2000h	0.85
Lumen maintenance at 4000h	0.78
Lumen maintenance at 6000h	0.76
Lumen maintenance at 8000h	0.75

Service Life

Average life	10000 h
Service Life	6500 h
Lamp survival factor at 2000h	0.99
Lamp survival factor at 4000h	0.99
Lamp survival factor at 6000h	0.95
Lamp survival factor at 8000h	0.81

Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	27 mm
Length	110 mm
Total length max.	110 mm
Length	110 mm

Compact fluorescent lamp Ralux® Duo

RX-D 10W/830/G24D

Radium

Specification

Burning position	h180
Mercury content	1.6 mg
Base	G24d-1
Colour	White

Notes on Operation

Burning position	h180
Ambient temperatures	-5 ... +40 °C

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	541285

Miscellaneous

EU-date of phase-out	25.02.2023
EU Directive	RoHS
Similar products	31317922

Notes


Compact fluorescent lamp, light colour 830, high luminous efficiency, good colour rendering, long life, base G24q. Controllable by Dim-ECG.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base



G24d
IEC/EN 60061-1
sheet 7004-78-5

Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K.


Every fluorescent lamp type has got an individual spectral power distribution according to its phosphor coating inside the bulb. From this result important properties light colour or colour rendering.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm) per 10nm.


Compact fluorescent lamp Ralux® Duo

RX-D 10W/830/G24D

Radium




light colour 830 Spectralux® Warm white (31)



daylight(D 65)

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.