High pressure sodium lamp RNP-E 70W/I/230/E27 MA



Product Datasheet Date: 06.09.2025











5900

2000K

24 000h

General Data

Article No.	34419992
Code	RNP-E 70W/I/230/E27 MA
Product EAN	4008597199929
Box quantitiy (pcs.)	24
EAN Box	4008597499920
Gross weight of box in kg	1.919
Length of box in m	0.36
Width of box in m	0.285
Height of box in m	0.355
Product weight	50 g
Product status	Active

Electric Parameters

Wattage	74.6 W
Lamp nominal wattage	70 W
Weighted energy consumption in 1000 hours	75 kWh
Lamp voltage	90 V
Mains voltage	220-240 V

High pressure sodium lamp RNP-E 70W/I/230/E27 MA



Electric Parameters

Ignition voltage	0.198	
Nominal current (A)	0.98 A	
Nominal choke current	1 A	_
Compensation capacitor for 50Hz operation	12 µF	
Fuse	Daelay-action; min. double nominal current	
dimmable	No	

Light Application Parameters

Luminous flux	5900 lm	
Rated lamp luminous flux	5900 lm	
Efficacy	79 lm/W	
Total mains efficacy	73 lm/W	
Colour temperature	2000 K	
Color coordinate X	0,535	
Color coordinate Y	0.420	
Color rendering index	< 25	
Lumen maintenance at 2000h	0.92	
Lumen maintenance at 4000h	0.86	
Lumen maintenance at 6000h	0.83	
Lumen maintenance at 8000h	0.82	
Lumen maintenance at 12000h	0.81	
Lumen maintenance at 16000h	0.81	
Lumen maintenance at 20000h	0.80	

Service Life

Average life	24000 h	
B5 - Service life 5% failures	12000 h	
B10 - Service life 10% failures	14000 h	
Lamp survival factor at 2000h	0.98	
Lamp survival factor at 4000h	0.97	
Lamp survival factor at 6000h	0.97	
Lamp survival factor at 8000h	0.96	
Lamp survival factor at 12000h	0.95	
Lamp survival factor at 16000h	0.85	
Lamp survival factor at 20000h	0.70	

High pressure sodium lamp

RNP-E 70W/I/230/E27 MA



Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	71 mm
Length max.	156 mm
Total length max.	156 mm
Burning position	h180
Mercury content	10.8 mg
Lamp shape	Ellipsoid
Model	Opal
Base	E27

Notes on Operation

Burning position	h180	

Information especially for EPREL

Energylabel notice	current label, with EPREL registration


Notes

Standard high pressure sodium lamp, elliptical bulb coated, base E27, Operation with ballast, no ignitor required.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Spectrum



Special features







General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment

High pressure sodium lamp

RNP-E 70W/I/230/E27 MA



valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.