



General Data

Article No.	OTNA5125
Code	DRIVER 250W/24V IP20
Product EAN	4003556015524
Box quantity (pcs.)	30
EAN Box	4003556415522
Gross weight of box in kg	19.3
Length of box in m	0.345
Width of box in m	0.28
Height of box in m	0.241
Product weight	576 g
Product status	● Active

Electric Parameters

Output power	0-250.0 W
Power factor	0.95
Input voltage AC (range)	198-264 V
Output voltage	24 V
Surge voltage resistance (L - N)	1 kV

Electric Parameters

Number of Channels	1
Standby consumption	0.5 W
Inrush current	46.4 A
Period of inrush current	680 µs
Input current max.	1.5 A
Output current	10400 mA
Mains frequency	50 / 60 Hz
Suitable for DC-voltage (primary side)	No
Content of harmonics (THD)	10 %
max. no. of lamps at 10A-B10 automatic fuse	2
max. no. of lamps at 16A-B16 automatic fuse	3
dimnable	No
Dimming with push-button	No

Service Life

Service life	50000 h
T _c Temperature max.	85 °C
Lifetime @T _c low	100000 h
Guarantee	5 years

Specification

Mean efficiency	93 %
Length	318 mm
Height max.	30 mm
Width	45 mm
Model	Static
Material	PC

Notes on Operation

Degree of protection (IP)	IP20
Protection class	II
Type of connection	spring clamp
Range of storage temperature	-20 ... +60 °C
Ambient temperatures	-20...+45 °C
T _c Temperature max.	85 °C
max. relative air humidity	90 %

Information especially for EPREL

Standby consumption

0.5 W

Miscellaneous

Similar products

OTNA3106, OTNA5124

Notes

Compact constant voltage LED driver for modules up to 250W, IP20, protection class II, easy to install

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.