


# Pear shape lamp 300°C, frosted

P 25W/230/300C/F/E14

# Radium

Product Datasheet Date: 31.05.2026



G



140



2700K



1 000h



Gradable

## General Data

Code Radium	19119443
Désignation	P 25W/230/300C/F/E14
EAN 10 (unité)	4008597194436
Unité de transport (pièces)	100
EAN 40 (carton)	4008597494437
Poids brut du carton en kg	1.061
Longueur box in m	0.285
Largeur du carton en m	0.15
Hauteur du carton en m	0.14
Product weight	8 g
Product status	<span style="color: red;">●</span> Inactif

## Electric Parameters

Wattage	25.0 W
Lamp nominal wattage	25 W
Weighted energy consumption in 1000 hours	25 kWh
Lamp voltage	220-240 V
Mains voltage	230 V

## Electric Parameters

dimnable	Oui
----------	-----

## Light Application Parameters

Luminous flux	140 lm
Rated lamp luminous flux	140 lm
Beam angle	360 °
Efficacy / Luminous efficiency	6 lm/W
Color temperature	2700 K
Color rendering index	100

## Service Life

Average life	1000 h
--------------	--------

## Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	26 mm
Length	57 mm
Total length max.	55 mm
Burning position	any
Lamp shape	Pear-shape
Model	Frosted
Base	E14
Colour	White

## Notes on Operation

Burning position	any
------------------	-----

## Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	533408

## Miscellaneous

Similar products	19119444
------------------	----------

# Pear shape lamp 300°C, frosted

P 25W/230/300C/F/E14

# Radium

## Notes


Pear-shape lamp frosted for higher temperatures up to 300°C (oven), base E14

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

## Culot




E14  
IEC/EN 60061-1  
sheet 7004-23-6

## Courbes spectrales


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




light of incandescent lamps



daylight(D 65)

## Particularités



## Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.