

# 1-10V Driver for DC-LED-Lamps/-Modules

DRIVER DC 1-10V 36W/200-400mA IP20

# Radium

Product Datasheet Date: 30.05.2026

## General Data

Code Radium	OTDA4970
Désignation	DRIVER DC 1-10V 36W/200-400mA IP20
EAN 10 (unité)	4003556014619
Unité de transport (pièces)	60
EAN 40 (carton)	4003556414617
Poids brut du carton en kg	7.5
Longueur box in m	0.317
Largeur du carton en m	0.203
Hauteur du carton en m	0.16
Product status	<span style="color: green;">●</span> Actif

## Electric Parameters

Output voltage	24 V
Suitable for DC-voltage (primary side)	Non
Dimming with push-button	Non

## Notes on Operation

Degree of protection (IP)	IP20
---------------------------	------

## Notes

Project goods, only available in large quantities upon request.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

# 1-10V Driver for DC-LED-Lamps/-Modules

DRIVER DC 1-10V 36W/200-400mA IP20

# Radium

## Particularités



## Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.