

LED Star+ Classic A, Filament

RL-A60 DIM HE 827/C/E27 FIL

Radium

Product Datasheet Date: 02.04.2026



A



2700K



50 000h



Gradable

General Data

Code Radium	44225334
Désignation	RL-A60 DIM HE 827/C/E27 FIL
EAN 10 (unité)	4008597253348
Unité de transport (pièces)	10
EAN 40 (carton)	4008597453342
Poids brut du carton en kg	0.58
Longueur box in m	0.31
Largeur du carton en m	0.13
Hauteur du carton en m	0.124
Product weight	36 g
Product status	● Actif

Electric Parameters

Wattage	4.0 W
Weighted energy consumption in 1000 hours	4 kWh
Lamp power	4.0 W
Nominal voltage	220-240 V
Voltage type	AC

Electric Parameters

Nominal current	19 mA
Nominal current (mA)	19 mA
Inrush current	2.84 A
max. no. of lamps at 10A automatic fuse	220
max. no. of lamps at 16A automatic fuse	352
dimnable	Oui

Light Application Parameters

Luminous flux	840 lm
Rated luminous flux according to IEC 62612	840 lm
Luminous flux	840 lm
Lumen-Output mark	HE
Beam angle	330 °
Efficacy	210 lm/W
Total mains efficacy	210 lm/W
Color temperature	2700 K
Color coordinate X	0.463
Color coordinate Y	0.420
Color rendering index	≥ 80
Color Stability	≤ 6 sdcn

Service Life

Average life	50000 h
Tc Temperature max.	60 °C
Mean service life	50000 h
Min. number of switching cycles	25000

Specification

Energylabel (G -> A)	A
Diameter	60 mm
Length	108 mm
Length	108 mm
Burning position	any
Material	Glass
Photobiological safety according to EN 62471	RG0
Lamp shape	Pear-shape

Specification

Base	E27
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	230 V
Ambient temperatures	-20 ... +40 °C
Tc Temperature max.	60 °C
With movement sensor	Non

Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Non
Type of color temperature	SINGLE_VALUE
Displacement factor EPREL	0,5
Life factor EPREL	0.9
Lumen maintenance EPREL	0.98
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	2422962

Notes

Standard LED lamp, energy efficiency class A (HE), clear glass bulb, dimmable, E27 base. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Courbes spectrales

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

LED Star+ Classic A, Filament

RL-A60 DIM HE 827/C/E27 FIL

Radium




LED-Retrofit-Lamps 2700K



daylight(D 65)

Particularités



Notices explicatives générales

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as that of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Consignes de sécurité

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.