

460

General Data

Code Radium	32317005
Désignation	HTC 400-221
EAN 10 (unité)	4008597170058
Unité de transport (pièces)	25
EAN 40 (carton)	4008597470059
Poids brut du carton en kg	0.6
Longueur box in m	0.18
Largeur du carton en m	0.18
Hauteur du carton en m	0.13
Product status	● Actif

Electric Parameters

Lamp power	460.0 W
Nominal power	460.0 W
Lamp voltage	135 V
Ignition voltage	3,0 - 4,5
Lamp's nominal current	4 A
Compensation capacitor for 50Hz operation	50 μ F

Light Application Parameters

Type of UV radiation	UV-A
----------------------	------

Specification

Diameter	17.5 mm
Tube diameter	14 mm
Length	104 mm
Total length max.	104 mm
Contact distance I	100.7 mm
radiator length (glass)	45 mm
Burning position	Random
Lamp shape	Tube, double-ended
Base	R7s

Notes on Operation

Burning position	Random
Generating ozone	Non
Suitable for air disinfection	Non
Suitable for water disinfection	Non

Notes


High-pressure UV lamp, for use only in enclosed fixtures and with control gear. Observe safety instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Courbes spectrales

Spektrale Strahlungsverteilung / spectral radiation distribution



Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or

High Pressure UV Lamps HTC

HTC 400-221

Radium

even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Consignes de sécurité

HTC lamps emit UV radiation. Intense exposure can cause corneal and/or conjunctival inflammation, as well as skin damage. Furthermore, these lamps become very hot during operation and operate at high pressure. Therefore, HTC lamps must only be used in designated, enclosed fixtures and not for general lighting. The safety instructions provided by the fixture manufacturer must be observed. This product contains mercury. In case of lamp breakage, follow the appropriate safety procedures and dispose of it properly after use.

All technical data without guarantee.