



General Data

| | |
|----------------|------------------|
| Code Radium | 32517061 |
| Désignation | RSI 2500W/SE G38 |
| EAN 10 (unité) | 4008597170614 |
| Product status | ● Actif |

Electric Parameters

| | |
|--------------|-----------|
| Lamp power | 2,500.0 W |
| Lamp voltage | 115 V |

Light Application Parameters

| | |
|-------------------------------|-----------|
| Luminous flux | 240000 lm |
| Colour temperature | 6000 K |
| Color rendering index nominal | 93 |

Service Life

| | |
|-------------------------------|-------|
| Service life | 750 h |
| B5 - Service life 5% failures | 250 h |

Specification

| | |
|-------------------|--------|
| Diameter | 60 mm |
| Total length max. | 225 mm |
| Burning position | Random |
| Mercury content | 215 mg |

Daylight lamp
RSI 2500W/SE G38

Radium

Base

G38

Notes on Operation

Burning position

Random

Notes

Hot-startable daylight lamp for sun simulation, stage or film, single-ended

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.