



LED Grid Luminaire Star, Panel 600

DALI 30W PS CCT UGR IP40

Radium

Product Datasheet Date: 30.05.2026



30004000K

General Data

Code Radium	PNLA5083
Désignation	PL S DALI 600 30W PS CCT UGR IP40
EAN 10 (unité)	4003556015135
Unité de transport (pièces)	6
EAN 40 (carton)	4003556415133
Poids brut du carton en kg	13.635
Longueur box in m	0.695
Largeur du carton en m	0.24
Hauteur du carton en m	0.618
Product weight	1770 g
Product status	● Actif

Electric Parameters

Factory setting wattage	30.0 W
Max. system power	30.0 W
Nominal voltage	220-240 V
Voltage type	AC
Factory setting lamp current	800 mA

Electric Parameters

Nominal current	152-800 mA
Nominal current (mA)	800 mA
Number of poles	2
Inrush current	7.93 A
Mains frequency	50/60 Hz Hz
Dimming with push-button	Non

Light Application Parameters

Luminous flux adjustable	Positions
Factory setting luminous flux	4500 lm
Luminous flux	4500 lm
Rated luminous flux according to IEC 62722-2-1	4500 lm
Luminous flux @3000K	2200-4180 lm
Luminous flux @4000K	2400-4500 lm
Beam angle adjustable	Non
Beam angle	85 °
Unified Glare Ratio (UGR)	19
Efficacy / Luminous efficiency	150 lm/W
Colour of light adjustable	Positions
Factory setting color temperature	4000 K
CCT Switch	Oui
Colour of light	White
Color temperature	3000 / 4000 K
Color coordinate X	0.382
Color coordinate Y	0.398
Color rendering index	≥ 80
Color Stability	≤ 3 sdcn
Light sharing	Symmetric
With light sensor	Non

Service Life

Lifetime L70B50	70000 h
Life L80B10	70000 h
No. switching cycles	≥ 100.000
Guarantee	5

Specification

Length	595 mm
Height/depth	34 mm
Width	595 mm
Material	Aluminium/ PS
Impact strength	IK02
Photobiological safety according to EN 62471	RG0
With light source	Oui

Notes on Operation

Degree of protection (IP)	IP40
Connection type	Push-in clamp
Type of wiring	Suitable for through wiring
Max. number of luminaires per B10 circuit breaker	32
Max. number of luminaires per B16 circuit breaker	42
Filament test according to IEC 60695-2-11	650 °C - 30 s
Type of control gear	LED operating device voltage-controlled
With light sensor	Non
With movement sensor	Non
Suitable for emergency lighting	Non
Emergency power supply integrated	Non

Information especially for EPREL

Contains a lightsource of energy efficiency class	C
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Oui
Type of color temperature	STEPS
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
EPREL ID number	2655152

Notes

Flat IP40 DALI LED retrofit panel 600x600 mm, integrated LED driver with power select, low glare (UGR), adjustable light color (steps)

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

LED Grid Luminaire Star, Panel 600

DALI 30W PS CCT UGR IP40

Radium

Particularités



Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.