

LED Grid Luminaire Essence, Panel 600

33W/840 IP40

Radium

Product Datasheet Date: 31.05.2026



4000K



3
YEARS
GUARANTEE

General Data

| | |
|-----------------------------|-----------------------|
| Code Radium | PNLA5072 |
| Désignation | PL E 600 33W/840 IP40 |
| EAN 10 (unité) | 4003556015029 |
| Unité de transport (pièces) | 6 |
| EAN 40 (carton) | 4003556415027 |
| Poids brut du carton en kg | 10.6 |
| Longueur box in m | 0.657 |
| Largeur du carton en m | 0.24 |
| Hauteur du carton en m | 0.618 |
| Product weight | 1290 g |
| Product status | ● Actif |

Electric Parameters

| | |
|----------------------|-----------|
| Max. system power | 33.0 W |
| Nominal voltage | 220-240 V |
| Voltage type | AC |
| Nominal current | 167 mA |
| Nominal current (mA) | 167 mA |

Electric Parameters

| | |
|--------------------------|-------------|
| Number of poles | 2 |
| Inrush current | 25.4 A |
| Mains frequency | 50/60 Hz Hz |
| Dimming with push-button | Non |

Light Application Parameters

| | |
|------------------------------------------------|-----------|
| Luminous flux adjustable | Non |
| Luminous flux | 4000 lm |
| Rated luminous flux according to IEC 62722-2-1 | 4000 lm |
| Beam angle adjustable | Non |
| Beam angle | 110 ° |
| Unified Glare Ratio (UGR) | 22 |
| Efficacy / Luminous efficiency | 120 lm/W |
| Colour of light adjustable | Non |
| CCT Switch | Non |
| Colour of light | White |
| Color temperature | 4000 K |
| Color coordinate X | 0.382 |
| Color coordinate Y | 0.398 |
| Color rendering index | ≥ 80 |
| Color Stability | ≤ 3 sdcn |
| Light sharing | Symmetric |
| With light sensor | Non |

Service Life

| | |
|----------------------|-----------|
| Lifetime L70B50 | 50000 h |
| Life L80B10 | 50000 h |
| No. switching cycles | ≥ 100.000 |
| Guarantee | 3 |

Specification

| | |
|-----------------|-----------------|
| Length | 595 mm |
| Height/depth | 33 mm |
| Width | 595 mm |
| Material | Steel sheet/ PS |
| Impact strength | IK02 |

LED Grid Luminaire Essence, Panel 600

33W/840 IP40

Radium

Specification

| | |
|----------------------------------------------|-----|
| Photobiological safety according to EN 62471 | RG0 |
| With light source | Oui |

Notes on Operation

| | |
|---------------------------------------------------|-----------------------------------------|
| Degree of protection (IP) | IP40 |
| Connection type | Push-in clamp |
| Type of wiring | Ending |
| Max. number of luminaires per B10 circuit breaker | 22 |
| Max. number of luminaires per B16 circuit breaker | 35 |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |
| Type of control gear | LED operating device voltage-controlled |
| With light sensor | Non |
| With movement sensor | Non |
| Suitable for emergency lighting | Non |
| Emergency power supply integrated | Non |

Information especially for EPREL

| | |
|---------------------------------------------------|--------------|
| Contains a lightsource of energy efficiency class | D |
| Mains/Non mains connectable | MLS |
| Directional or non-directional light | NDLS |
| Color tunable light source | Non |
| Type of color temperature | SINGLE_VALUE |
| Flickering value Pst LM | 1 |
| Stroboscope effect value SVM | 0.4 |
| EPREL ID number | 2655166 |

Notes

Flat IP40 LED retrofit panel 600x600 mm, 33W with integrated LED driver, low glare, light color 4000K

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Particularités



Notices explicatives générales

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case

LED Grid Luminaire Essence, Panel 600

33W/840 IP40

Radium

of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.