
RL-T8 18 S 8,9W/840/G13 HF



Product Datasheet Date: 03.12.2025















E 1100

4000K 50 000h

General Data

| Article No. | 42918103 |
|---------------------------|----------------------------|
| Codice | RL-T8 18 S 8,9W/840/G13 HF |
| Product EAN | 4008597181030 |
| Box quantitiy (pcs.) | 25 |
| EAN Box | 4008597481031 |
| Gross weight of box in kg | 3.814 |
| Length of box in m | 0.73 |
| Width of box in m | 0.17 |
| Height of box in m | 0.18 |
| Product weight | 94 g |
| Product status | Inattivo |

Electric Parameters

| Wattage | 8.9 W |
|---|-----------|
| Weighted energy consumption in 1000 hours | 11 kWh |
| Lamp power | 8.9-8.9 W |
| Power factor | > 0,9 |
| Nominal voltage | 220-240 V |

RL-T8 18 S 8,9W/840/G13 HF



Electric Parameters

| Mains Voltage | 220 - 240 V |
|----------------------|-------------|
| Voltage type | AC |
| Nominal current | 340-340 mA |
| Nominal current (mA) | 340 mA |
| dimmable | No |

Light Application Parameters

| Rated lamp luminous flux | 1100 lm | |
|-----------------------------|------------|--|
| Luminous flux in 90°-sector | 1100 lm | |
| Beam angle | 160 ° | |
| Efficacy | 123.6 lm/W | |
| Total mains efficacy | 123.6 lm/W | |
| Color temperature | 4000 K | |
| Color rendering index | > 80 | |
| Color Stability | ≤ 6 sdcm | |

Service Life

| Average life | 50000 h |
|----------------------|---------|
| Tc Temperature max. | 75 °C |
| Mean service life | 50000 h |
| No. switching cycles | 200000 |

Specification

| Energylabel notice | old label, no EPREL registration, no EU data sheet |
|------------------------|--|
| Energylabel (G -> A) | E |
| Energylabel (E -> A++) | A+ |
| Diameter | 28 mm |
| Tube diameter | 26 mm |
| Length | 590 mm |
| Length | 590 mm |
| Burning position | any |
| Mercury content | 0.0 mg |
| Material | Glass |
| Shatterproof | Sì |
| Lamp shape | Tube, double-ended |
| Base | G13 |

RL-T8 18 S 8,9W/840/G13 HF



Specification

| Colour | White |
|--------|-------|
| | |

Notes on Operation

| Degree of protection (IP) | IP20 |
|------------------------------|-----------|
| Burning position | any |
| Mode of operation | ECG |
| Range of storage temperature | -20+80 °C |
| Ambient temperatures | -20 +50°C |
| Tc Temperature max. | 75 °C |

Information especially for EPREL

| Energylabel notice | old label, no EPREL registration, no EU data sheet |
|----------------------------|--|
| Lighting technology | LED |
| Color tunable light source | No |
| Type of color temperature | SINGLE_VALUE |

Notes

T8 tubular LED lamp for exchange with fluorescent lamps, neutral white light, plastic body, non-dim, base G13. Operation with suitable ECG.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base



Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.


White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.

RL-T8 18 S 8,9W/840/G13 HF





LED retrofit tube lamps for fluorescent lamps 4000K



daylight(D 65)

Special features









General notes

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.