
# LED Essence Tube
RL-T8 58 21,5W/865/G13

Radium

Product Datasheet Date: 01.11.2026






| A | 2100 | 6500K | 30 000h |
|---|---|---|---|

## General Data

| | |
|---|---|
| Article No. | 42818013 |
| Codice | RL-T8 58 21,5W/865/G13 |
| Product EAN | 4008597180132 |
| Box quantitiy (pcs.) | 8 |
| EAN Box | 4008597480133 |
| Gross weight of box in kg | 3.523 |
| Length of box in m | 1.62 |
| Width of box in m | 0.14 |
| Height of box in m | 0.07 |
| Product weight | 361 g |
| Product status | Inattivo |

## Electric Parameters

| | |
|---|---|
| Wattage | 21.5 W |
| Weighted energy consumption in 1000 hours | 26 kWh |
| Lamp power | 21.5-21.5 W |
| Power factor | > 0,9 |
| Power factor | 0.9 |

# LED Essence Tube
RL-T8 58 21,5W/865/G13

Radium

## Electric Parameters

| | |
|---|---|
| Nominal voltage | 220-240 V |
| Voltage type | AC |
| Nominal current | 95-95 mA |
| Nominal current (mA) | 95 mA |
| max. no. of lamps at 10A-B10 automatic fuse | 70 |
| max. no. of lamps at 16A-B16 automatic fuse | 112 |
| dimmable | No |

## Light Application Parameters

| | |
|---|---|
| Rated lamp luminous flux | 2100 lm |
| Luminous flux in 90°-sector | 2100 lm |
| Beam angle | 150 ° |
| Efficacy / Luminous efficiency | 97.67 lm/W |
| Total mains efficacy | 97.67 lm/W |
| Color temperature | 6500 K |
| Color rendering index | ≥ 80 |
| Color Stability | ≤ 6 sdcm |

## Service Life

| | |
|---|---|
| Average life | 30000 h |
| Mean service life | 30000 h |
| No. switching cycles | 200000 |

## Specification

| | |
|---|---|
| Energylabel notice | old label, no EPREL registration, no EU data sheet |
| Energylabel (E -> A++) | A |
| Diameter | 28 mm |
| Tube diameter | 26 mm |
| Length | 1500 mm |
| Length | 1500 mm |
| Burning position | any |
| Mercury content | 0.0 mg |
| Shatterproof | No |
| Photobiological safety according to EN 62471 | RG0 |
| Lamp shape | Tube, double-ended |
| Base | G13 |

# LED Essence Tube
RL-T8 58 21,5W/865/G13

Radium

## Specification

| | |
|---|---|
| Material | Glass |
| Colour | White |
| Housing colour | White |

## Notes on Operation

| | |
|---|---|
| IP Class (Room/Ceiling) | IP20 |
| Burning position | any |
| Mode of operation | CCG, 230V |
| Range of storage temperature | -20…+80 °C |
| Ambient temperatures | -20 ... +45°C |
| With movement sensor | No |

## Information especially for EPREL


| | |
|---|---|
| Energylabel notice | old label, no EPREL registration, no EU data sheet |
| Lighting technology | LED |
| Mains/Non mains connectable | MLS |
| Directional or non-directional light | NDLS |
| Color tunable light source | No |
| Type of color temperature | SINGLE_VALUE |
| Displacement factor EPREL | 0,7 |
| Life factor EPREL | 0.9 |
| Lumen maintenance EPREL | 0.96 |
| Flicker | 1.0 |
| Stroboscopic effect | 0.4 |

## Notes

T8 tubular LED lamp for exchange with fluorescent lamps, daylight, plastic body, non-dim, base G13. Please, note installation instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

**Base**




G13
IEC/EN 60061-1
sheet 7004-51-8

**Spectrum**


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

# LED Essence Tube
RL-T8 58 21,5W/865/G13

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED-Retrofit-Tube-Lampen für Leuchtstofflampen 6500K




daylight(D 65)

**Special features**




**General notes**
Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

**Safety instructions**
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

**All technical data without guarantee.**